

Features

- Lift lever ratio up to 1:20 – 200 kg with only 10 kg of effort
- For use with aluminium profiles 40 mm and 45 mm
- Protectively covered foot pedal
- Generously dimensioned levelling foot for stable standing
- Flexible movement of heavy loads
- Safe standing for all works

RS PRO Castor Wheels

RS Stock No.: 250-0426



RS PRO is the own brand of RS. The RS PRO Seal of Approval is your assurance of professional quality, a guarantee that every part is rigorously tested, inspected, and audited against demanding standards. Making RS PRO the Smart Choice for our customers.

Product Description

Reliable and quiet swivel castor, trackless with ball bearings and thread guard integrated mounting plate for fixation to aluminium profiles with modular dimension 40 and 45 mm without overhang, no additional transport and base plate needed; roller movement locking by temporary positioning on lifting foot, actuation of the height adjustment of the lifting foot via foot pedal on the swivel castor housing

General Specifications

Rotation	Braked Swivel and braked rotation
Weight Class	Heavy duty load capacity
Load Capacity	250KG
Load Capacity / 4pcs	1000kg
Tyre Material	PA white
Hub Material	Steel
Bracket Material	Steel
Includes Brake	Yes
Features	Corrosion Resistant, Impact Resistant, Shock Absorbing
Applications	Vending machines, Medical appliances, Workstations, Measuring Instruments

Mechanical Specifications

Mounting Type	Multiple bolt holes
Wheel Diameter	80mm
Overall Height	125mm
Number of Fixing Holes	4
Fixing Hole Size	8mm
Hub Bearing Type	Ball bearing
Levelling Extent	12mm
Castor Weight	2.4Kg

Fixing Centres Specifications	
Fixing Centres	77.1mm by 89mm
Fixing Centres (Length)	89mm
Fixing Centres (Width)	77.1mm

Fixing Plate Specifications	
Fixing Plate Dimensions	134mm by 110mm
Fixing Plate Length	134mm
Fixing Plate Width	110mm

