



ENGLISH

# Datasheet

## RS Pro Tap Wrenches: T-Bar Type Ratchet Type

RS Stock No: 2300113



### Specifications:

Ratchet Type

T-handles slide both ways for tightening

Hardened & tempered split collet chucks for positive grip

Knurled & hardened clamping nut

Spring tension holds handle in desired position

Handle: 127mm

Height: 94mm

A/F Range: 3-5mm

| Order Code | Manufacturers Code | Description              |
|------------|--------------------|--------------------------|
|            | 4311-226           | Tap Wrenches: T-Bar Type |



ENGLISH

# Datasheet

## RS Pro Tap Wrenches: T-Bar Type

## Ratchet Type

Tap Range:

| Square     | ISO 529           | ISO 529        | DIN 352       | ISO 529 | ISO 529 | ISO 529 | ISO 529 | ISO 529 | ANSI |
|------------|-------------------|----------------|---------------|---------|---------|---------|---------|---------|------|
| Dimensions | Metric Coarse     | Metric Coarse  | Metric Coarse | BSW     | BSF     | UNC     | UNF     | BA      | NPT  |
|            | Full Diameter     | Relieved Shank |               |         |         |         |         |         |      |
|            | Shank with Recess |                |               |         |         |         |         |         |      |
| Size mm    | Size              | Size           | Size          | Size    | Size    | Size    | Size    | Size    | Size |
| 3          |                   |                |               |         |         |         |         |         |      |
| 3.15       | M4                | M5             |               | 5/32    |         |         |         |         |      |
| 3.3        |                   |                | M4            |         |         |         |         |         |      |
| 3.5        |                   |                |               |         |         |         |         | 3       |      |
| 3.55       | M4.5              | M6             |               |         |         |         |         |         |      |
| 3.8        |                   |                | M4.5          |         |         |         |         |         |      |
| 4          | M5                |                |               | 3/16    | 3/16    |         |         | 2       |      |
| 4.2        |                   |                | M5            |         |         |         |         |         |      |
| 4.5        |                   | M7             |               |         |         |         |         |         |      |
| 4.9        |                   |                |               |         |         |         |         | 0       |      |
| 5          | M6                | M8             | M6            | 1/4     | 1/4     | 1/4     | 1/4     |         |      |