

AP8659EU3

Rack PDU 2G, Metered by Outlet with Switching, ZeroU, 16A, 230V, (21) C13 & (3) C19



Overview

Presentation	APC Metered by Outlet with Switching Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and individual outlet power metering. Remote outlet level controls allow power on/off functionality for power recycling to reboot locked-up equipment and to avoid unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, and locking IEC receptacles. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.
Lead time	Usually in Stock

Main

Colour	Black
PDU type	Switched metered outlet
Cable length	3.00 m
Provided equipment	CAN port terminator Installation guide Locking input power cord Rack mounting brackets Safety guide Serial configuration cable

Complementary

Main Input Voltage	200 V 208 V 230 V
Height	182.9 cm
Width	5.6 cm
Main Output Voltage	230 V
Depth	5.1 cm
Net weight	6.77 kg
Mounting location	Side
Mounting preference	No preference
Input Connection Type	IEC 60309 16 A 2P + E
Mounting mode	Not rack-mountable
Number of rack unit	0U
Mounting position	Vertical
Permissible voltage	100...240 V
Input current limits	16 A

Load capacity	3700 VA
Network frequency	50/60 Hz
Number of power socket outlets	21 IEC 60320 C13 3 IEC 60320 C19



Environment

Product certifications	PSE[RETURN]UL listed[RETURN]VCCI class A[RETURN]VDE
Standards	EN 55022 class A EN 55024 EN 61000-3-2 EN 61000-3-3 FCC part 15 class A ICES-003
Ambient air temperature for operation	-5...60 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	203.8 cm
Package 1 Width	16.2 cm
Package 1 Length	11.7 cm
Package 1 Weight	9.031 kg

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Lead free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------