



## Stumpy Lid – All Colours

### Part Number 100500 -100509

Colour coded high quality OilSafe Stumpy Spout Lid, designed for use with any of the 3, 5, or 10 litre Oilsafe drums. Will not bend, break, warp or leak. 25 mm outlet spout opening. This lid is for pouring larger lubricant flow applications with a large handle for easy carrying and for hanging when required. Auto shut off breather valve to avoid accidental spillage or contamination through breathers that are left open. Advanced thread & sealing design ensures secure fully sealing fit to all genuine OilSafe cans, guaranteeing audit compliance.

- With a 1 inch spout opening, the OilSafe Stumpy Spout Lid design is ideal for applications where a higher lubricant flow is required.
- Match with a Stumpy Extension Hose to help with hard to reach fill points.
- Available in 10 different colours, providing you broad range for quick and easy fluid identification and prevention of misapplication risk.
- The Stumpy Spout Lid includes a large handle for ease of carrying and a auto shut off breather valve to avoid accidental spillage or contamination.
- Made with state-of-the-art materials, the Stumpy Spout Lid has an advanced sealing thread design that ensures a secure fit on all OilSafe Drums. It's made with industrial grade, heat resistant materials.
- The ultra durable construction will not warp, leak or break.
- Weight: 1.04 lbs

#### Further Information:

|                                    |                                                                                |
|------------------------------------|--------------------------------------------------------------------------------|
| <b>Type</b>                        | Stumpy Spout Lid                                                               |
| <b>Brand</b>                       | OilSafe                                                                        |
| <b>Diameter</b>                    | 147.3 mm / 5.8"                                                                |
| <b>Spout length</b>                | 139.7 mm / 5.5"                                                                |
| <b>Weight</b>                      | 471.74 gram / 1 lbs                                                            |
| <b>Material</b>                    | High Density Polyethylene (HDPE)                                               |
| <b>Remark</b>                      | NOT SUITABLE FOR USE WITH FUELS OR SOLVENTS                                    |
| <b>Minimal service temperature</b> | -40 °C / -40 °F                                                                |
| <b>Maximum service temperature</b> | 80 °C / 176 °F                                                                 |
| <b>Additives</b>                   | UV Stabiliser Anti Static Additive Sealing Components: Nitrile O Ring (Buna N) |
| <b>Country of Manufacture</b>      | United States                                                                  |