




ENGLISH

Datasheet

IEC PVC Insulated Flat Pair Thermocouple Extension & Compensating Cable

PVC Insulated Flat Pair (to IEC-584)



- PVC insulated flat pair construction
- Conductors laid flat PVC insulated with overall PVC sheath
- All round general purpose cable, both waterproof and very flexible
- Thermocouple extension types for K, J, T & N
- Compensating types VX (KCB) & U (RCA) for types K & R/S Thermocouples respectively
- Stranded conductors available, either 7/0.2mm, 13/0.2mm or 23/0.2mm
- Available in 10, 25, 100 & 200 metre lengths
- Tolerance Class 2
- Insulation rating -10°C to 105°C
- Colour code (cores & jacket) to IEC-584-3

Compensating cable resembles the thermoelectric characteristic of the relevant thermocouple over a limited ambient temperature range, 0° to 80°C typically. Since these cables are made from low cost materials, cost savings can be achieved on plant installations compared with running true thermocouple extension cable.

Extension cable (true thermocouple material) should be used for maximum accuracy.

	Conductors	Cores	Jacket	Reel Length	Allied Code	RS order code					
Extension:											
KX	7/0.2mm	+Green/-White	Green	10 metres	70657084	827-5615					
KX	7/0.2mm	+Green/-White	Green	25 metres	70641729	236-3820					
KX	7/0.2mm	+Green/-White	Green	50 metres	70657085	827-5619					
KX	7/0.2mm	+Green/-White	Green	100 metres	70646156	611-7889					
KX	7/0.2mm	+Green/-White	Green	200 metres	70657088	827-5628					
KX	13/0.2mm	+Green/-White	Green	10 metres		2154893					
KX	13/0.2mm	+Green/-White	Green	25 metres		827-5883					
KX	13/0.2mm	+Green/-White	Green	50 metres		827-5892					
KX	13/0.2mm	+Green/-White	Green	100 metres		2154894					
KX	23/0.2mm	+Green/-White	Green	25 metres		185-3004					
EX	7/0.2mm	+Purple/-White	Purple	10 metres		136-5863					
EX	7/0.2mm	+Purple/-White	Purple	25 metres		136-5864					
JX	7/0.2mm	+Black/-White	Black	10 metres	70641640	219-4753					
JX	7/0.2mm	+Black/-White	Black	25 metres	70657078	827-5592					
JX	7/0.2mm	+Black/-White	Black	50 metres	70657079	827-5596					
JX	7/0.2mm	+Black/-White	Black	100 metres	70641737	236-3915					
JX	7/0.2mm	+Black/-White	Black	200 metres	70657081	827-5606					
TX	7/0.2mm	+Brown/-White	Brown	10 metres	70641637	219-4703					
TX	7/0.2mm	+Brown/-White	Brown	25 metres	70641734	236-3870					
TX	7/0.2mm	+Brown/-White	Brown	50 metres	70657095	827-5653					
TX	7/0.2mm	+Brown/-White	Brown	100 metres	70651749	762-1146					
TX	7/0.2mm	+Brown/-White	Brown	200 metres	70657098	827-5662					
TX	13/0.2mm	+Brown/-White	Brown	25 metres		827-5899					
NX	7/0.2mm	+Pink/-White	Pink	10 metres	70641635	219-4668					
NX	7/0.2mm	+Pink/-White	Pink	25 metres	70657091	827-5637					
NX	7/0.2mm	+Pink/-White	Pink	50 metres	70657089	827-5631					
NX	7/0.2mm	+Pink/-White	Pink	100 metres	70657092	827-5640					

	Conductors	Cores	Jacket	Reel Length	Allied	RS order code
					Code	
Compensating:						
VX (KCB)	7/0.2mm	+Green/-White	Green	10 metres	70657082	827-5609
VX (KCB)	7/0.2mm	+Green/-White	Green	25 metres	70641629	219-4551
VX (KCB)	7/0.2mm	+Green/-White	Green	50 metres	70657080	827-5603
VX (KCB)	7/0.2mm	+Green/-White	Green	100 metres	70641630	219-4573
VX (KCB)	7/0.2mm	+Green/-White	Green	200 metres	70657083	827-5612
VX (KCB)	13/0.2mm	+Green/-White	Green	10 metres	70657086	827-5621
VX (KCB)	13/0.2mm	+Green/-White	Green	25 metres	70657087	827-5625
VX (KCB)	13/0.2mm	+Green/-White	Green	50 metres	70657090	827-5634
VX (KCB)	13/0.2mm	+Green/-White	Green	100 metres	70651750	762-1152
U (RCA)	7/0.2mm	+Orange/-White	Orange	10 metres	70657096	827-5656
U (RCA)	7/0.2mm	+Orange/-White	Orange	25 metres	70646158	611-7902
U (RCA)	7/0.2mm	+Orange/-White	Orange	50 metres	70657097	827-5659
U (RCA)	13/0.2mm	+Orange/-White	Orange	10 metres	70641641	219-4769
U (RCA)	13/0.2mm	+Orange/-White	Orange	25 metres	70657093	827-5643

U (RCA) 13/0.2mm +Orange/-White Orange 50 metres 70657094 **827-5647**