E8232L1F_LS_G2

1 way switch, Pieno, 16AX, 250V, 2 gang, with fluorescent locator, Lavendar Silver





Main	
Range	Pieno
Product or component type	Switch
Device application	Control
Switch application	Switch
Load type	Resistive Fluorescent
Cover frame colour tint	Lavender silver

Complementary

Device mounting	Surface	
G	Flush	
Switch function	1-way	
Number of rocker	2	
Rated current	16 AX at 250 V AC 50 Hz	
Local signalling	Fluorescent	
Material	Polycarbonate: surround	
	Polycarbonate: grid plate	
Connections - terminals	Pillar terminals	
Clamping connection capacity	2 x 1.5 mm² for stranded cable(s)	
	2 x 2.5 mm² for solid cable(s)	
Embedding depth	23 mm	
Width	87 mm	
Height	87 mm	
Depth	23 mm	

Environment

Ambient air temperature for operation	-540 °C
Relative humidity	095 %
Standards	GB 16915.1 MS IEC 60669-1 BS EN 60669-1
	IEC 60669-1 SS 227-1

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.6 cm	
Package 1 Width	8.7 cm	
Package 1 Length	8.7 cm	
Package 1 Weight	96 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	8	
Package 2 Height	15 cm	

Package 2 Width	19 cm
Package 2 Length	8 cm
Package 2 Weight	764 g
Unit Type of Package 3	CAR
Number of Units in Package 3	80
Package 3 Height	21 cm
Package 3 Width	32.5 cm
Package 3 Length	50 cm
Package 3 Weight	7644 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	[™] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations