



# SAFETY JOGGER

## INDUSTRIAL



## PROIMPACT SINGLE 4X42CP

### PROIMPACTS Impact Gloves

Safety Jogger PRO IMPACT gloves deliver advanced impact protection and comfort for assembly, automotive, industry and construction tasks.

|                   |                                                                              |
|-------------------|------------------------------------------------------------------------------|
| Performance level | 4X42CP                                                                       |
| Liner             | 13 Gauge/HPPE/Polyamide/Polyester/Glass Fibre/Spandex                        |
| Coating           | Foam Nitrile                                                                 |
| Category          | TSF-Touchscreen function, SIF-Silicone Free                                  |
| Size range        | EU 7-12                                                                      |
| Sample weight     | 0.078 kg                                                                     |
| Norms             | ANSI/ISEA 105:2016<br>ANSI/ISEA 138-2019<br>EN ISO 21420:2020<br>EN 388:2016 |



EN ISO 21420

EN 388:2016



### Industries:

Automotive, Assembly, Construction, Industry

### Impact resistant

These gloves have extra padding to protect your palms and knuckles from impacts, reducing the risk of injury.

### Excellent cut resistance

These gloves provide excellent protection against cuts, meeting the second-highest level of cut resistance according to the EN 388 standard. They are ideal for tasks with a higher risk of cuts.



514

### Performance level 4X42CP

| EN388:2016                      | 0     | 1   | 2   | 3    | 4    | 5    |
|---------------------------------|-------|-----|-----|------|------|------|
| a. Abrasion resistance (cycles) | < 100 | 100 | 500 | 2000 | 8000 | -    |
| b. Cut resistance (Coup test)   | < 1.2 | 1.2 | 2.5 | 5.0  | 10.0 | 20.0 |
| c. Tear resistance (newton)     | < 10  | 10  | 25  | 50   | 75   | -    |
| d. Puncture resistance (newton) | < 20  | 20  | 60  | 100  | 150  | -    |

| EN ISO 13997 (TDM-100 test)                     | A | B | C  | D  | E  | F  |
|-------------------------------------------------|---|---|----|----|----|----|
| e. Straight blade cut resistance (TDM 100 test) | 2 | 5 | 10 | 15 | 22 | 30 |

- a. Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- b. Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- c. Tear resistance: based on the amount of force required to tear the sample.
- d. Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- e. Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.

**SAFETY  
JOGGER**  
WORKS

**HEAD-TO-TOE  
PROTECTION**

ENGINEERED  
IN EUROPE

[www.safetyjogger.com](http://www.safetyjogger.com)

