

Datasheet

## RS Pro Plain Stainless Steel Countersunk Head Machine Screws, M3 x 20mm

RS Stock No: **158-3590**



### Product Details

RS Pro machine screw measuring M3 x 20 mm, is made of type 316 S16 plain A4 grade 18//8 stainless steel, which has higher level of corrosion resistance than A2 stainless steel. The countersunk head screw can be used at up to 300°C. The cross drive screw is suitable for use in food, medical, chemical, construction and electronic applications. This machine screw meets DIN965 standards.

### Features and Benefits

- A4 grade 18/8 stainless steel (Type 316 S16) construction
- Higher level of corrosion resistance than A2 S/S
- Suitable for use up to 300°C
- Suitable for use in most food, medical, chemical, construction and electronic applications

**Specifications:**

|                      |                 |
|----------------------|-----------------|
| Drive Type           | Pozidriv        |
| Finish               | Plain           |
| Head Shape           | Countersunk     |
| Material             | Stainless Steel |
| Length               | 20 mm           |
| Stainless Steel Type | 316 (A4)        |
| Thread Pitch         | 0.5             |
| Thread Size (Metric) | M3              |
| Head Diameter        | 5.2 to 5.5 mm   |
| Head Height          | 1.65 mm         |
| Recess Diameter      | 1.76 to 2.01 mm |
| Specification        | DIN 965         |