



Revision Number: 009.0

Issue date: 08/21/2017

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product name:</b>	<b>LOCTITE SI 587 BLUE RTV SILICONE GASKET known as LOCTITE® 587™ FLANGE SEALANT</b>	<b>IDH number:</b>	234592
<b>Product type:</b>	Silicone Sealant	<b>Item number:</b>	58791
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	Canada
<b>Company address:</b>	<b>Contact information:</b>		
Henkel Canada Corporation	Telephone: (905) 814-6511		
2515 Meadowpine Boulevard	MEDICAL EMERGENCY Phone: Poison Control Center		
Mississauga, Ontario L5N 6C3	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**WARNING:** MAY CAUSE AN ALLERGIC SKIN REACTION.  
CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A
SKIN SENSITIZATION	1

**PICTOGRAM(S)**



**Precautionary Statements**

<b>Prevention:</b>	Avoid breathing dust or fumes. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.
<b>Response:</b>	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Wash contaminated clothing before reuse.
<b>Storage:</b>	Not prescribed
<b>Disposal:</b>	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

IDH number: 234592      Product name: LOCTITE SI 587 BLUE RTV SILICONE GASKET known as LOCTITE® 587™ FLANGE SEALANT

Hazardous Component(s)	CAS Number	Weight %*
Limestone	1317-65-3	30 - 40
Amorphous fumed silica	68611-44-9	5 - 10
Butan-2-one O,O',O''-(vinyilsilyldyne)trioxime	2224-33-1	1 - 5
Quartz (SiO <sub>2</sub> )	14808-60-7	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Move to fresh air in case of accidental inhalation of vapours or decomposition products. If symptoms develop and persist, get medical attention.
<b>Skin contact:</b>	Wipe off paste with paper towel or cloth. Wash with soap and water. If skin irritation persists, call a physician.
<b>Eye contact:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If adverse health effects develop seek medical attention.
<b>Ingestion:</b>	Do not induce vomiting. In case of adverse health effects seek medical advice.
<b>Symptoms:</b>	See Section 11.

#### 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Prevent inhalation of fumes and gases. Wear self-contained breathing apparatus.
<b>Unusual fire or explosion hazards:</b>	Not available.
<b>Hazardous combustion products:</b>	Oxides of carbon. Oxides of silicon. Formaldehyde. Irritating organic vapours.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow product to enter sewer or waterways.
<b>Clean-up methods:</b>	Scrape up as much material as possible. Maintain good ventilation for large spills. Place scrap material in a well ventilated area and allow to cure to rubber.

#### 7. HANDLING AND STORAGE

<b>Handling:</b>	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation.
<b>Storage:</b>	For safe storage, store at or below 32 °C (89.6 °F) Keep container closed.

**Shelf Life Statement: Not available.**

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Limestone	10 mg/m3 TWA Total dust.	5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Amorphous fumed silica	None	0.8 mg/m3 TWA 20 MPPCF TWA	None	None
Butan-2-one O,O',O''-(vinylsilylidyne)trioxime	None	None	None	None
Quartz (SiO <sub>2</sub> )	0.025 mg/m3 TWA Respirable fraction.	2.4 MPPCF TWA Respirable. 0.1 mg/m3 TWA Respirable. 0.05 mg/m3 TWA (Respirable dust.) (Respirable dust.) 0.025 mg/m3 OSHA_ACT (Respirable dust.) 0.05 mg/m3 PEL Respirable dust.	None	None

<b>Engineering controls:</b>	Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.
<b>Respiratory protection:</b>	Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.
<b>Eye/face protection:</b>	Safety goggles or safety glasses with side shields. Safety showers and eye wash stations should be available.
<b>Skin protection:</b>	Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Paste
<b>Color:</b>	Blue
<b>Odor:</b>	Mild, Petroleum
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not applicable
<b>Vapor pressure:</b>	< 5 mm hg (20 °C (68°F))
<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	1.31 at 20 °C (68°F)
<b>Vapor density:</b>	Not available.
<b>Flash point:</b>	> 93 °C (> 199.4 °F) Tagliabue closed cup
<b>Flammable/Explosive limits - lower:</b>	Not available.
<b>Flammable/Explosive limits - upper:</b>	Not available.
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not available.
<b>Solubility in water:</b>	Polymerises in presence of water.
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	3.33 %; 43.09 g/l
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable at normal conditions.
<b>Hazardous reactions:</b>	None under normal processing.
<b>Hazardous decomposition products:</b>	Oxides of carbon. Oxides of silicon. Methyl ethyl ketoxime formed during cure. Formaldehyde.
<b>Incompatible materials:</b>	Oxidizing agents. Acids and bases.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Exposure to moisture.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes, Ingestion

**Potential Health Effects/Symptoms**

<b>Inhalation:</b>	May cause respiratory tract irritation. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release.
<b>Skin contact:</b>	May cause skin irritation. May cause allergic skin reaction.
<b>Eye contact:</b>	Causes serious eye irritation.
<b>Ingestion:</b>	Not expected under normal conditions of use. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Limestone	None	Nuisance dust
Amorphous fumed silica	None	No Target Organs
Butan-2-one O,O',O''-(vinylysilyldyne)trioxime	None	Irritant, Allergen
Quartz (SiO2)	None	Immune system, Lung, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Limestone	No	No	No
Amorphous fumed silica	No	No	No
Butan-2-one O,O',O''-(vinylysilyldyne)trioxime	No	No	No
Quartz (SiO2)	Known To Be Human Carcinogen.	Group 1	Yes

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Cured rubber can be incinerated or landfilled following EPA and local regulations. Follow all local, state, federal and provincial regulations for disposal.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### Canada Transportation of Dangerous Goods - Ground

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### Water Transportation (IMO/IMDG)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None  
**Exceptions:** None

## 15. REGULATORY INFORMATION

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2, 3, 8, 11

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 08/21/2017

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.