



ENGLISH

Datasheet Impact Wrenches

3/4 inch Compact Air Impact Wrench

[RS Stock No. 739-8373](#)



Specifications

Power source	: Compressed air
Maximum permissible operating pressure	: 90 psi (6.2 bar)
Recommended operating pressure	: 90 psi (6.2 bar)
Material	: Aluminium
Size	: 3/4"
Max Torque	: 1350Nm / 1000 ft-lb
Vibration	: 4.96m/s ² Sound: 108dBA
Mechanism	: Pin Clutch Hammer
Free Speed	: 3,800RPM
Length	: 10" / 250mm
Weight	: 5.2kgs / 11.46lbs
Min Hose Size	: 1/2" / 13mm
Air Inlet thread	: 3/8"
Ave Air Consumption	: 10cfm / 282 l/min
Recommended lubrications	: 10 Weight SAE Oil

Features:

- High power output
- Pin clutch hammer mechanism
- Forward and reverse mode
- Rear exhaust through handle
- 3 forward & 3 reverse operating impact settings
- Non slip comfortable grip
- Ideal for truck, bus and farm machinery work
- Rugged design
- Single handed direction change

Declaration of Conformity

We RS Components Ltd declare under our sole 739-8373 – 3/4" Impact Wrench responsibility that the conforms with the directive 2006/42/EEC and the standards EN 792-6 ISO 28927