




Benefits

- Perfectly designed as replacement for traditional halogen lamps which deliver perfect light to create the desired atmosphere
- Offer linear dimming which is compatible with most leading-edge and trailing-edge EU dimmers
- Enhance efficacy, beam control and excellent optics by Hybrid Reflector Technology

Application




Model	Item Description	W	PF	lm	lm/W	CRI	Beam Angle	Life (h)	Single Box (LxWxH)mm	Outer Box (LxWxH)mm	Packing Qty (PCS/CTN)
LR057055/dm-HRv00-WF	PAR16 5.5W GU10 HR 2800K 36D DIM	5.5	0.7	500	91	80	35°	25000	55*55*65	294*244*230	60
LR057055/dm-HRv00-WF	PAR16 5.5W GU10 HR 4000K 36D DIM	5.5	0.7	500	91	80	35°	25000	55*55*65	294*244*230	60

Application Conditions	
IP	IP20
Operating Temperature	-20~40°C
Application Temperature	25°C
Storage Environment	-25~50°C


Mechanical Properties	
Optical Material	PC
Housing Material	PBT
Finishing Colour	Grey

Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	220-240
AC/DC	AC

Photometric Data



Dimensional Drawing



LR057055/dm-HRv00-WF