

FEATURES

- Miniature crocodile clips also known as spring clip
- Crocodile clip has PP Insulated material - provides full insulation with good plug compatibility
- Nickel-Plated brass - offers good resistance to corrosion
- Choice of colours - red and black clips are available
- Temperature Range -25°C to +100°C
- Capable of clamping flat components with the specifically shaped nose
- Clamping wires up to a max of 4mm
- Current Rating 8A up to 30V AC or 60VDC
- Designed to be used with a standard 2mm banana plug

RS PRO Crocodile Clip

RS Stock No.: 2121203, 2121204



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Miniature Insulated crocodile clip.
 Spring loaded, nickel plated, brass jaws, allows a secure contact to be made when clamping wires up to a maximum diameter of 4mm.
 Also capable of clamping flat components.
 Available in Red and Black

General Specifications

Contact Material	Brass
Contact Plating	Nickel
Housing Material	Poly propylene
Spring	Stainless Steel

Electrical Specifications

Voltage Rating	30VAC / 60VDC
Contact Resistance	5 mΩ
Rated Current	8A
Measurement cat. acc. to IEC61010	CAT 1

Mechanical Specifications

Type of termination	Spring-loaded socket Ø 2mm
Type of contact	Clamp

Operation Environment Specifications

Operating Temperature	-25°C to +100°C
------------------------------	-----------------

Inflamability Rating

Inflammability class	UL 94 HB
-----------------------------	----------

Note: UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETRES

LINEAR & RADIAL TOLERANCE: NO DECIMAL PLACES 0.2mm

1 DECIMAL PLACE 0.1mm 2 DECIMAL PLACES 0.05mm

ANGULAR TOLERANCE: 1

THE FINISHED PRODUCT SHOULD BE CLEAN AND FREE FROM ALL LIQUIDS AND DEBRIS. SURFACES SHOULD BE OF UNIFORM APPEARANCE FREE FROM SHARP EDGES, BURRS AND CORROSION

