

FEATURES

- Material: UL approved Nylon 66, 94V-2
- Color: Grey (RAL7035)available in other colors.
- Suit a variety of applications, and diverse industries.
- Function :Mount gland to pre-drilled panel hole, use locknut to fix gland on board, insert the cables in the seal,and then tighten up the nut to hold cables in position.
- Simply and quickly fixed, high degree of the protection IP68 preventing dust and water.

RS PRO Cable Gland

RS Stock No.: 214-1076



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

RD PRO

- Material: UL approved Nylon 66, 94V-2
- Color: Grey(RAL7035), available in other colors.
- Suit a variety of applications, and diverse industries.
- Function :Mount gland to pre-drilled panel hole, use locknut to fix gland on board, insert the cables in the seal,and then tighten up the nut to hold cables in position.
- Feature : Simply and quickly fixed, high degree of the protection IP68 preventing dust and water.
- Available to order the accessories separately. Follow the drawing and add the letter to the suffix part number, L for locknut, W for washer, B for gland body, S for seal, N for nut.

General Specifications

Series	Metric Thread					
Туре	Cable Gland					
Colour	Grey(RAL7035)					
Material	Nylon 66					
Finish						
Application						
Resistant To						
UV Resistant	No					
Minimum Operating Temperature	-40°C					
Maximum Operating Temperature	85°C					
Fire Behaviour	Self-Extinguishing					
Quantity	50pc					

Mechanical Specifications	
Thread	M20 x P1.5
Mounting Hole	20.0~20.3 mm
Cable Range	10 ~ 14 mm

Cable Gland



 Protection Category

 IP Rating
 IP68 (only if the locknut and washer are assembled)

Approvals	
Declarations	
Standards Met	UL, RoHS, CE, HF

Similar Products



RS Article	Thread	Mounting Hole	D1	D2	B1	L1	L2	L3	Cable Range	Packing
2141076	M20xP1.5	20.0~20.3	20	15	14	15	29	19	10 ~ 14	50PCS

** IP68 (only if the locknut and washer are assembled)

