

FEATURES

- Quick connection and disconnection
- Large range to comply food norms
- Silicon
- Operating temperature range is from - 15 °C to + 190 °C

RS PRO STRAIGHT MALE ADAPTOR (PARALLEL) -FOOD GRADE

RS Stock No.: 2312744



RS PROfessionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Pneumatic Quick Connect Couplings



Product Description

The RS PRO straight male adaptor (parallel) works in - 0.99 bar to 20 bar pressure range. It is mainly used in dairy, coffee machine, vending, food & beverage, medical, vacuum applications. It is available in brass with Food Grade coating. In combination with FEP tubes, it is the most demanded solution for the Food & Beverage market. Beacause of the special coating it can be used also in agressive environment.

RoHS and REACH compliant.

General Specifications

Material	Nickel Plated Brass		
Applications	Lubrication System, Cooling System, Pneumatic		
Applications	Machinery Equipment		

Mechanical Specifications

Connection Type	Threaded, Tube 4mm			
Hose Barb Connection				
Coupling Gender	Male 1/8 in Male 1/8in 4mm 13mm			
Threaded Connection				
Thread Size				
Hose Barb Connection				
Mounting Hole Diameter				
Wrench Size1	10			
Wrench Size2	2			
Length	21mm			




Operation Environment Specifications

Minimum Operating Temperature	-15°C
Maximum Operating Temperature	190°C

Similar Products

Parameters	2312742	2312745		
Brand	RS PRO	RS PRO		
Connection Type	Threaded, Tube	Threaded, Tube		
Hose Barb Connection	4mm	6mm		
Coupling Gender	Male	Male		
Threaded Connection	M5 Male	1/8 in Male		
Thread Size	M5mm	1/8in		
Hose Barb Connection	8	6mm		
Mounting Hole Diameter	10	13mm		
Wrench Size1	2	13		
Wrench Size2	21mm	4		
Length	Threaded, Tube	23.5mm		





Tube	Α	В	С	L	CH1	CH2	Pack.
4	1/8	5.4	13	20	10	3	10