



## TELMIG 203/2



### Overview

#### TELMIG 203/2

cod. 821060

MIG-MAG welding machine. Designed for continuous and spot welding with electronic regulation of spotwelding time. Flexibility of use with a wide range of materials such as steel, stainless steel, highstrength steels and aluminium. Complete with MIGMAG welding accessories.



3 PH 230V-400V



CE MARKING



EAC CERTIFICATION



COIL 15 kg

### Technical data

CODE	CODE 821060	MAX NO LOAD VOLTAGE	31 V	STEEL WELDING WIRE DIAMETER	0,6 - 1 mm
THREE PHASE MAINS VOLTAGE	230 / 400 V	MAX ABSORBED POWER	5,5 kW	INOX WELDING WIRE DIAMETER	0,8 mm
MAINS FREQUENCY	50 / 60 Hz	ABSORBED POWER AT 60%	3 kW	ALUMINIUM WELDING WIRE DIAM.	0,8 - 1 mm
CURRENT RANGE	25 - 200 A	MAINS FUSE	10 / 6 A	PROTECTION DEGREE	IP21
MAX CURRENT DC (EN 60974-1)	160 @ 25 % A	POWER FACTOR (cosphi)	0,9	DIMENSIONS	80 x 45 x 65,5 cm
DC CURRENT	105 A	ADJUSTMENT POSITIONS	6	WEIGHT	44 kg

### Included Accessories

null - 124467



TOLEDO 250 WORK CLAMP 250A - 712030



 **TELMIG 203/2**

SPACER - 322499



ARGON GAS BOTTLE IT ADAPTOR - 432036



GAS REGULATOR REFILLABLE BOTTLE - 722341

MT15 MIG TORCH 3M (RED) - 742180