

FEATURES

- Coil spring design for strength and elasticity
- Wire diameter ends up to 0.8mm are squared and unground
- Wire diameter ends 1.00mm and over are squared and ground
- Manufactured with a right hand helix
- Spring can be directly put on the rod products

RS PRO Steel Alloy Compression Spring, 30.5mm x 7.3mm, 3.26N/mm

RS Stock No.: 751-578



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

A range of compression springs from our RS PRO offer which come in various sizes and lengths and with closed and ground and closed not ground end types. Compression springs are very popular as they can store a large amount of energy in a small space making them ideal for a great range of uses.

General Specifications

| | |
|---------------------|-----------------------------------------------------------------------|
| Materials | Steel Alloy |
| Ends | Closed |
| Applications | Ball point pens, Vehicles, Mobile phones, Valves, Electrical switches |

Mechanical Specifications

| | |
|---------------------------------------|----------|
| Outside Diameter | 7.3mm |
| Wire Diameter | 1mm |
| Free Length | 30.5mm |
| Minimum Working Length | 19.9mm |
| Load at Minimum Working Length | 34.13N |
| Spring Rate | 3.26N/mm |

Approvals

| | |
|----------------------------------|--------------------|
| Compliance/Certifications | DIN 2095 (grade 2) |
|----------------------------------|--------------------|



| RS Stock No. | Free Length | Outside Diameter | Spring Rate | Minimum Working Length |
|--------------|-------------|------------------|-------------|------------------------|
| 751499 | 38.5 mm | 5.63 mm | 0.7N/mm | 16.2 mm |
| 751506 | 54 mm | 6.93 mm | 0.63N/mm | 17.7 mm |
| 751534 | 36 mm | 5.8 mm | 1.8N/mm | 21.5 mm |
| 751540 | 68 mm | 8.8 mm | 0.44N/mm | 23.8 mm |
| 751556 | 45.5 mm | 10.8 mm | 0.49N/mm | 14.3 mm |
| 751562 | 34.5 mm | 6 mm | 4.4N/mm | 24.6 mm |
| 751578 | 30.5 mm | 7.3 mm | 3.26N/mm | 19.9 mm |
| 751584 | 28.5 mm | 9 mm | 2.33N/mm | 14.3 mm |
| 751590 | 59 mm | 9 mm | 1.08N/mm | 28.3 mm |
| 751607 | 26 mm | 11 mm | 1.85N/mm | 11.2 mm |
| 751613 | 56 mm | 11 mm | 0.81N/mm | 22.4 mm |
| 751629 | 55.5 mm | 13.5 mm | 0.61N/mm | 19.4 mm |
| 751641 | 22 mm | 9.25 mm | 8.92N/mm | 10.5 mm |
| 751657 | 69 mm | 9.25 mm | 2.69N/mm | 30 mm |