



! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product WEICONLOCK AN 302-45
Code-Nr. 302450

**1.2. Relevant identified uses of the substance or mixture and uses advised against
Recommended intended purpose(s)**

1-Component Adhesives and Sealants, anaerobic curing

1.3. Details of the supplier of the safety data sheet

Distributor WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244
E-Mail : msds@weicon.de
Internet : www.weicon.de

Advice Produktsicherheit / Product-Safety-Department
Phone : +49(0)251 / 9322 - 0
Fax : +49(0)251 / 9322 - 244
E-mail (competent person):
msds@weicon.de

1.4. Emergency telephone number

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:
++44 1865 407333 (English)
TRANSPORT EMERGENCY CONTACT - UK, UAE, South
Africa (24h): Tel: ++44 1865 407333 (English)

Manufacturer WEICON GmbH & Co. KG
Königsberger Str. 255, DE-48157 Münster

1.4. Emergency telephone number

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):
Tel: ++49 69 222 25285 (Deutsch, Englisch)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard categories Hazard Statements Classification procedure

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H335

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

2.2. Label elements**Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]**

GHS07

! Signal word

Warning

Hazard Statements

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Precautionary Statements

P102	Keep out of reach of children.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container to hazardous or special waste collection point.

! Hazardous ingredients for labeling

2-hydroxyethyl methacrylate, cumene hydroperoxide

2.3. Other hazards**Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

! SECTION 3: Composition/ information on ingredients**3.1. Substances**

not applicable

3.2. Mixtures**Description**

Anaerobic adhesive / sealant



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 04.01.2019 (GB) Version 8.5

WEICONLOCK AN 302-45

! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
868-77-9	212-782-2	2-hydroxyethyl methacrylate	5 - 10	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317
107-21-1	203-473-3	ethanediol	1 - 5	Acute Tox. 4, H302
80-15-9	201-254-7	cumene hydroperoxide	1 - 5	Org. Perox. E, H242 / Acute Tox. 3, H331 / Acute Tox. 4, H312 / Acute Tox. 4, H302 / STOT RE 2, H373 / Skin Corr. 1B, H314 / Aquatic Chronic 2, H411
117-83-9	204-213-1	BIS(2-BUTOXYETHYL)PHTHALATE	10 < 25	Aquatic Chronic 4, H413

REACH

CAS No	Name	REACH registration number
868-77-9	2-hydroxyethyl methacrylate	01-2119490169-29
107-21-1	ethanediol	01-2119456816-28
80-15-9	cumene hydroperoxide	01-2119475796-19

Additional advice

CAS: 80-15-9: STOT SE3; H335: 1% < C < 10%

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

If swallowed give water to drink.

4.2. Most important symptoms and effects, both acute and delayed

Physician's information / possible symptoms

Allergic symptoms

skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

! SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam

Dry fire-extinguishing substance

Carbon dioxide

sand

Water spray jet

! Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO₂)**5.3. Advice for firefighters****Special protective equipment for fire-fighters**

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.

! SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Ensure adequate ventilation.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

! SECTION 7: Handling and storage**7.1. Precautions for safe handling****! Advice on safe handling**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

**Hygiene measures**

At work do not eat, drink and smoke.

Remove soiled or soaked clothing immediately.

Wash hands before breaks and after work.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep only in original container.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with oxidizing agents.

Do not store together with reducing agents.

Further information on storage conditions

Store at +5 till +25 °C.

Protect from heat and direct solar radiation.

Store container at cool and aired place.

7.3. Specific end use(s)**Recommendation(s) for intended use**

See section 1.2

! SECTION 8: Exposure controls/personal protection**8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
107-21-1	Ethane-1,2-diol: particulate	8 hours	10		EH40/2005
107-21-1	Ethane-1,2-diol: vapour	8 hours	52	20	EH40/2005
		Short-term	104	40	

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
107-21-1	ethanediol	8 hours	52	20	skin
		Short-term	104	40	

DNEL-/PNEC-values**DNEL worker**

CAS No	Substance name	Value	Code	Remark
80-15-9	cumene hydroperoxide	6 mg/m ³	DNEL long-term inhalative (systemic)	
868-77-9	2-hydroxyethyl methacrylate	4,9 mg/m ³	DNEL long-term inhalative (systemic)	
		1,3 mg/kg bw/day	DNEL long-term dermal (systemic)	

PNEC

CAS No	Substance name	Value	Code	Remark
868-77-9	2-hydroxyethyl methacrylate	3,79 mg/kg	PNEC soil, freshwater	
		10 mg/l	PNEC sewage treatment plant (STP)	



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 04.01.2019 (GB) Version 8.5

WEICONLOCK AN 302-45

DNEL-/PNEC-values (continued)

CAS No	Substance name	Value	Code	Remark
		0,482 mg/l	PNEC soil, marine water	

Additional advice

The statutory local and national regulations have to be observed.

8.2. Exposure controls

Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Breathing apparatus in the event of aerosol or mist formation.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: fluorinated rubber; 0,7mm; 480min; 60min;

Eye protection

tightly fitting goggles

Other protection measures

protective clothing

Appropriate engineering controls

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

liquid

Colour

blue

Odour

pungent

Odour threshold

not determined

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not determined				
melting point	not determined				
Flash point	> 100 °C				
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	not determined				



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 04.01.2019 (GB) Version 8.5

WEICONLOCK AN 302-45

	Value	Temperature	at	Method	Remark
Self ignition temperature					The product is not self-igniting.
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined				
Relative density	1,1 g/ml				
Vapour density	not determined				
Solubility in water					low soluble
Solubility/other				Organic solvent	teilweise mischbar
Partition coefficient n-octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity	ca. 20000 mPa*s	25 °C			thixotropic
Oxidising properties	No information available.				
Explosive properties	no				
9.2. Other information	No information available.				

! SECTION 10: Stability and reactivity**10.1. Reactivity**

No hazardous reactions known.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

Reactions with strong oxidising agents.

Reactions with reducing agents.

Reactions with Metals.

10.4. Conditions to avoid

Metal, Metal-Salts

Keep away from heat.

10.5. Incompatible materials**! Substances to avoid**

radical former

Oxidising agent, strong

Reducing agent, strong



Metal, Metal-Salts

10.6. Hazardous decomposition products

Gases/vapours, toxic

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

! SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
LD50 acute oral	382 mg/kg	rat	estimate	CAS: 80-15-9
LD50 acute dermal	1100 mg/kg		estimate	CAS: 80-15-9
LC50 acute inhalation	3 mg/l ()		estimate	CAS: 80-15-9
Skin irritation	irritant			
Eye irritation	irritant - risk of strong eye injuries			
Skin sensitization	sensitizing			

Subacute Toxicity - Carcinogenicity

	Value	Species	Method	Validation
Mutagenicity				No experimental information on genotoxicity in vitro available.
Reproduction-Toxicity				No indications of toxic effects were observed in reproduction studies in animals.
Carcinogenicity				No indications of carcinogenic effects are available from long-term trials.

Experiences made from practice

Sensitization through skin contact possible.

Risk of strong eye injuries.

Irritates eyes and skin.

! Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

No toxicological data available.

**SECTION 12: Ecological information****12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
Fish	LC50 3,9 mg/l (96 h)	rainbow trout		CAS: 80-15-9
Daphnia	EC50 > 100 mg/l (48 h)	Daphnia magna		CAS: 107-21-1
Algae	NOEC > 400 mg/l (72 h)	Selenastrum capricornutum		CAS: 868-77-9
Bacteria	EC20 1995 mg/l (0,5 h)	activated sludge		CAS: 107-21-1

12.2. Persistence and degradability

	Elimination rate	Method of analysis	Method	Validation
Biological degradability	90 - 100 % (10 d) CAS: 107-21-1			Biodegradable
Degradability	84 % (28 d) CAS: 868-77-9			readily degradable

12.3. Bioaccumulative potential

No information available.

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects**General regulation**

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into the ground water or aquatic environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this was derived from products of similar structure or composition.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Waste code No.**

08 04 09*

Name of waste

waste adhesives and sealants containing organic solvents or other hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.



SECTION 14: Transport information

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	-	-	-
14.2. UN proper shipping name	-	-	-
14.3. Transport hazard class(es)	-	-	-
14.4. Packing group	-	-	-
14.5. Environmental hazards	-	-	-
14.6. Special precautions for user	No information available.		
14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	not applicable		
Transport/further information	No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.		

! SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

VOC content	ca.3 %
VOC value	25,1 g/L

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

! SECTION 16: Other information

! Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.
For industrial use only.

Further information

Each user is responsible for the implementation of the national special regulations.
The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.
Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.4

H242	Heating may cause a fire.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 04.01.2019 (GB) Version 8.5

WEICONLOCK AN 302-45

-
- H373 May cause damage to organs (or state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.