



## Main

|                             |               |
|-----------------------------|---------------|
| Range                       | New Unica     |
| Product or component type   | Socket-outlet |
| Device presentation         | Mechanism     |
| Device mounting             | Flush         |
| Socket number               | 1             |
| Outlet poles configuration  | 2P + E        |
| Outlet standard             | French        |
| Outlet standard description | Pin earth     |
| Rated current               | 16 A          |

## Complementary

|                                |   |
|--------------------------------|---|
| Device application             | Power supply  |
| Cover type                     | With shutter  |
| [Ue] rated operational voltage | 250 V   |
| Network type                   | AC  |
| Network frequency              | 50/60 Hz  |
| Number of modules              | 2 modules   |
| Fixing mode                    | Clip-in   |
| Colour tint                    | Anthracite (RAL 7021)   |
| Connections - terminals        | Screwless terminals   |
| Cable cross section            | 0...2.5 Mm <sup>2</sup> cable(s), 2 - cable stiffness: flexible<br>0...2.5 mm <sup>2</sup> cable(s), 2 - cable stiffness: rigid |
| Minimum load breaking capacity | 100 operations 1.25 In and 1.1 Un, cos phi = 0.6  |
| Electrical durability          | 10000 cycles, cos phi = 0.8   |
| Insulation resistance          | > 5 MOhm at 500 V   |
| Dielectric strength            | 2000 V  |
| Material                       | PC: mechanism cover   |
| Surface finish                 | Painted   |
| Quantity per set               | Set of 1 without packaging  |
| Standards                      | IEC 60884-1<br>NF C 61-314  |
| Product certifications         | NF  |
| Embedding depth                | 28.7 mm   |
| Depth                          | 38 mm   |
| Width                          | 45 mm   |
| Height                         | 45 mm   |
| Product weight                 | 0.03 kg   |

|                               |   |
|-------------------------------|---|
| Surface treatment             | Painted   |
| Resistance to chemical agents | Resistant to alcohol (70 %)<br>Resistant to alcohol (96 %)<br>Resistant to A-Lactic Acid<br>Resistant to diluted quaternary ammonium<br>Resistant to diluted bleach<br>Resistant to diluted ammonia<br>Resistant to soapy water<br>Resistant to crystal cleaner<br>Resistant to hydrogen peroxide 10 volumes<br>Resistant to hexane |

## Environment

|                                       |   |
|---------------------------------------|---|
| Ambient air temperature for operation | -5...35 °C  |
| Ambient air temperature for storage   | -5...50 °C  |
| IK degree of protection               | IK04  |
| IP degree of protection               | IP4X  |
| Environmental characteristic          | Acetone<br>Bleach<br>UV resistant<br>Petrol<br>Oil<br>Alcohol<br>Window-cleaning fluid<br>Liquid soap |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 3.9 cm   |
| Package 1 Width              | 4.5 cm   |
| Package 1 Length             | 4.5 cm   |
| Package 1 Weight             | 31.0 g   |
| Unit Type of Package 2       | BB1      |
| Number of Units in Package 2 | 10       |
| Package 2 Height             | 8.0 cm   |
| Package 2 Width              | 18.0 cm  |
| Package 2 Length             | 25.0 cm  |
| Package 2 Weight             | 412.0 g  |
| Unit Type of Package 3       | S04      |
| Number of Units in Package 3 | 140      |
| Package 3 Height             | 30.0 cm  |
| Package 3 Width              | 40.0 cm  |
| Package 3 Length             | 60.0 cm  |
| Package 3 Weight             | 6.542 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| Cradle to Cradle           |  Bronze                                  |
| REACH Regulation           |  REACH Declaration                       |
| EU RoHS Directive          | Compliant  EU RoHS Declaration           |
| Mercury free               | Yes   |
| China RoHS Regulation      |  China RoHS Declaration                  |
| RoHS exemption information |  Yes                                     |
| Environmental Disclosure   |  Product Environmental Profile           |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |