# Product data sheet Characteristics

# LV432594

Long terminal shield, ComPacT NSX400/630, pitch 45mm, IP40, 4 poles





# Main

Product or component type	Long terminal shield
Range compatibility	ComPacT new generation (ComPacT NSX400 new generation) ComPacT new generation (ComPacT NSX630 new generation) ComPact (ComPact NSX400) ComPact (ComPact NSX630) ComPacT new generation (ComPacT NSX DC new generation) NSX400 DC ComPacT new generation (ComPacT NSX DC new generation) NSX630 DC ComPact Compact NSX400 DC ComPact Compact NSX630 DC EasyPact (EasyPact CVS400) EasyPact (EasyPact CVS630) ComPact (Compact INV) ComPact (ComPacT INS)
Accessory / separate part type	Insulation accessories
Poles description	4P
Quantity per set	1

#### Complementary

in promonery	
Connection pitch	45 mm
IP degree of protection	IP40 conforming to IEC 60529

### **Packing Units**

racking office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.100 cm
Package 1 Width	11.200 cm
Package 1 Length	22.000 cm
Package 1 Weight	323.000 g
Unit Type of Package 2	S04
Number of Units in Package 2	15
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	5.504 kg
Unit Type of Package 3	P12
Number of Units in Package 3	60
Package 3 Height	50.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	34.204 kg

# Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile

# Contractual warranty

Warranty	18 months
wantanty	TO MONUIS