

Datasheet

RS Pro 1.1 kW Manual 3PST DOL Starter, 240 V, 1 Phase, IP55

RS Stock No: **909-4089**



Product Details

RS Pro 1.1 kW manual 3PST DOL starter with steel enclosure, measures 104 x 174 x 134 mm. It has a range of enclosed direct-on-line motor starter which combine high performance and low cost. The range support motors from 0.75 kW to 7.5 kW. It is complete with thermal overload that is fitted for quick easy installing.

Features and Benefits

- Operating temperature range: -5 to +40°C
- Range available as 1-phase or 3-phase model
- Voltage rating of 240 V
- 3-phase 3 PST
- DOL starter
- Compliant with standards BSEN60947-Pt4-Sec 1, BSEN60529-1992 and IEC947-4-1

Specifications:

| | |
|-----------------------------|----------------------------------------------------------------------------------------|
| Additional Features | Colour RAL 7035 Light Grey, Hand Reset Thermal Overloads, Provision for Remote Control |
| Enclosure | Yes |
| Motor Starter Functionality | Manual |
| Motor Starter Type | DOL |
| Phase | 1 |
| Standards Met | BS EN 60947/60529; IEC 947 |
| Overall Depth | 134 mm |
| Overall Length | 104 mm |
| Overall Width | 174 mm |
| IP Rating | IP55 |
| Mounting Type | Surface Mount |
| Number of Poles | 3 |
| Power Rating | 1.1 kW |
| Voltage Rating | 240 V ac |
| Motor Supporting Range | 0.75 to 7.5 kW |
| Operating Temperature | -5 to +40°C |