

6181Y / BS 6004 Cable

multicomp PRO

**RoHS
Compliant**



Application

Fixed installation in dry or damp areas for domestic and light industrial wiring. Also used in connection to (smart) meters.

Characteristics

Voltage Rating (Uo/U) : 300/500V
Temperature Rating : Fixed: -15°C to +70°C
Minimum Bending Radius : Fixed: 4 × overall diameter
Insulation Colour : Blue, Brown
Sheath Colour : Grey

This product range is available on reels of 50m or per metre.

Cable Standards

BS 6004, BS EN/IEC 60332-1-2

Construction

Conductor

Class 2 stranded copper conductor according to BS EN 60228 (previously BS 6360)

Insulation

PVC (Polyvinyl Chloride) Type T11 according to BS EN 50363

Sheath

PVC (Polyvinyl Chloride) Type 6 according to BS EN 50363

Dimensions

Nominal Cross Sectional Area mm ²	Nominal Diameter of Conductor mm	Nominal Thickness of Insulation mm	Nominal Overall Diameter mm
25	5.9	1.2	11.1

Class 2 Stranded Conductor for Single Core and Multi-Core Cables

Nominal Cross Sectional Area mm ²	Minimum No. of Wires in Conductor						Maximum Resistance of Conductor @ 20°C	
	Circular		Circular Compacted		Shaped		Annealed Copper Conductor	
	Cu	Al	Cu	Al	Cu	Al	Plain Wires Ω/km	Metal Coated Wires Ω/km
25	7	7	6	6	6	6	0.727	0.734

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
Element14.com/multicomp-pro

multicomp PRO

Electrical Characteristics

Current Carrying Capacity

Nominal Cross Sectional Area mm ²	Reference Method A (Enclosed in Conduit in Thermally Insulating Wall ETC) Amps		Reference Method B (Enclosed in Conduit on a Wall or in a Trunking ETC) Amps		Reference Method C (Clipped Direct) Amps	
	2 Cables Single-Phase AC or DC	3 or 4 Cables Three-Phase AC	2 Cables Single-Phase AC or DC	3 or 4 Cables Three-Phase AC	2 Cables Single-Phase AC or DC Flat or Touching	3 or 4 Cables Three-Phase AC Flat, Touching or trefoil
25	80	73	101	89	114	104

Nominal Cross Sectional Area mm ²	Reference Method F (In free Air on a Perforated Cable Tray Horizontal & Vertical) Amps				
	Touching			Spaced by one diameter	
	2 Cables Single-Phase AC or DC Flat	3 Cables Three-Phase AC Flat	3 Cables Three-Phase AC trefoil	2 Cables Single-Phase AC or DC or 3 Cables Three-Phase AC flat	
				Horizontal	Vertical
25	131	114	110	146	130

Ambient Temperature: 30°C

Conductor Operating Temperature: 70°C

The above table is in accordance with Table 4D1A of the 17th Edition of IEE Wiring Regulations.

Voltage Drop

Nominal Cross Sectional Area mm ²	2 Cables DC mV/A/m	2 Cables Single-Phase AC mV/A/m								
		Reference Methods A and B (enclosed in conduit or trunking)			Reference Methods C and F (clipped direct, on tray or in free air)					
					Cables Touching			Cables Spaced*		
		r	x	z	r	x	z	r	x	z
25	1.75	1.8	0.33	1.8	1.75	0.2	1.75	1.75	0.29	1.8

Nominal Cross Sectional Area mm ²	3 or 4 Cables Three-Phase AC mV/A/m											
	Reference Methods A and B (enclosed in conduit or trunking)			Reference Methods C and F (clipped direct, on tray or in free air)								
				Cables Touching, Trefoil			Cables Touching, Flat			Cables Spaced*, Flat		
	r	x	z	r	x	z	r	x	z	r	x	z
25	1.5	0.29	1.55	1.5	0.175	1.5	1.5	0.25	1.55	1.5	0.32	1.55

Conductor Operating Temperature: 70°C

r = Resistive Component; x = Reactive Component; z = Impedance Value

* Spacing larger than one cable diameter will result in larger volt drop.

De-Rating Factors

For Ambient Air Temperatures other than 30°C

Ambient Temperature	25°C	30°C	35°C	40°C	45°C	50°C	55°C	60°C
De-Rating Factor	1.03	1	0.94	0.87	0.79	0.71	0.61	0.5

Part Number Table

Description	Part Number
6181Y / BS 6004 Cable, Grey/Blue	PP002118
6181Y / BS 6004 Cable, Grey/Brown	PP002119

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.