



**Datasheet**  
**Stock No: 763-7444**

**ENGLISH**

# ZIKD 2.5 BG Three Level Feed Through Motor Connection Terminal



## Description

Three level terminal, feed through, 3 x 2 connections with tension spring connection system.

## Type and Features

- Type: ZIKD 2.5
- Connection Type: Tension spring
- Colour: BG (grey)
- Material of insulated housing: PA 6.6
- Temperature range: -40 to +120 °C
- Number of cross connection channels: 3
- Test pick-off: 6

## Ratings

- Rated voltage (V): IEC 500; CSAus 300; CSA 300
- Rated current (A): IEC 24; CSAus 15; CSA 15
- Rated wire cross-section: 2.5 mm<sup>2</sup> (20-12 AWG)
- Rated impulse voltage: 6 kV
- Plug gauge acc. to EN60947-1: A3
- Flammability class to UL 94: V0

## Connection Data

- Single wire (solid): 0.5 - 4 mm<sup>2</sup>
- Stranded: 0.5 - 4 mm<sup>2</sup>
- Stranded with ferrules: 0.5 - 2.5 mm<sup>2</sup>
- Contact wire range: 0.08 – 4 mm<sup>2</sup>
- Stripping length: 10 mm

## Accessory

- RS 899-7839: End plate