


Ultra-Fast Switching

High efficiency Glass Passivated Rectifier

multicomp PRO



Features:

- Fred chip construction
- Soft recovery characteristics
- Low forward voltage drop
- Low reverse leakage current
- High surge current capability
- Plastic material has UL flammability classification 94V-0

Mechanical Data:

Case : ITO-220AB, molded plastic
 Terminals : Pure tin plated, Lead Solderable per MIL-STD-750, Method 2026
 Polarity : As marking
 Mounting Position : Any
 Forward Current : 16 Amperes

Maximum Ratings and Electrical Characteristics:

Rating at 25°C ambient temperature unless otherwise specified.
 Single phase, half wave, 60Hz, resistive or inductive load.
 For capacitive load, derate current by 20%.

Characteristics	Symbol	MURF1620CT	MURF1660CT	Unit
Max. Recurrent Peak Reverse Voltage	VRRM	200	600	V
Max. RMS Voltage	VRMS	140	420	
Max. DC Blocking Voltage	VDC	200	600	
Max. Average Forward Rectified Current	IF(AV)	16		A
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Super Imposed on Rated Load (JEDEC Method)	IFSM	100		
Max. Forward Voltage at 8A per leg	VF	1	1.7	V
Max. DC Reverse Current at TJ = 25°C Rated DC Blocking Voltage at TJ = 125°C	IR	5 250		µA
Typical Thermal Resistance Junction to Ambient	RθJA	60		°C/W
Typical Thermal Resistance Junction to Case	RθJC	4		
Maximum Reverse Recovery Time (IF = 0.5A, IR = 1.0A, IRR = 0.25A)	TRR	35	50	Ns
Operating Temperature Range	TJ	-55 to +150		°C
Storage Temperature Range	TSTG			

Notes:

The typical data above is for reference only

Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 Element14.com/multicomp-pro


multicomp PRO

Ultra-Fast Switching


High efficiency Glass Passivated Rectifier

multicomp PRO


Ratings and Characteristic Curves




Forward Current Derating Curve



Typical Forward Characteristics



Min. Non-repetitive Peak Fwd Surge Current




Typical Reverse Characteristics

Ultra-Fast Switching

High efficiency Glass Passivated Rectifier

multicomp PRO

Dimensions:



Part Number Table

Description	Part Number
Ultra-Fast Switching, High Efficiency Glass Passivated Rectifiers	MURF1620CT
	MURF1660CT

Dimensions : Inches (Millimetres)

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
 Farnell.com/multicomp-pro
 Element14.com/multicomp-pro

multicomp PRO