SPST Push Switch






Specifications


Rating : 16A 125/250V~(cURus)


16(4)A 250V ~ T125/55 (ENEC15/CQC)

Withstand Voltage: 1,000V AC 1 minuteContact Resistance: 20mΩ initial (Max.)Insulation Resistance: 500V DC - 100MΩ (Min.)


Diagram








Dimensions : Inches/Millimetres Tolerances ±0.012"/0.3mm





X (Panel Thickness)	Y (Cutout Dimension)	Z (Cutout Dimension)
0.75mm to 1.25mm	19.2 +0/-0.1mm	
1.25mm to 2mm	19.4 +0/-0.1mm	12.9 +0.15/-0mm
2mm to 3mm	19.8 +0/-0.1mm	

Part Number Table

Description	Base Colour	Actuator Colour	Part Number
SPST Push Switch	Black	Black	MCPS-5-1M0-PNBB-SC
		Red	MCPS-5-1M0-PNBR-SC(B0RE)

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

