

## MIT300 Series Insulation and Continuity Testers



- Extremely easy to use
- Tough rubber armoured case
- Self contained protective cover
- Live circuit warning
- Weatherproof to IP54
- Intelligent Safety System for protection.
- Result storage and downloading
- Download software included
- USB interface

### DESCRIPTION

The Megger MIT300 series features:

**Digital or Analogue:** The Megger MIT300, MIT310 and MIT320 all feature the popular Megger digital/analogue display. Large 20mm high characters provide very clear readout, combined with an analogue arc for the feel of an analogue instrument, with a true analogue response.

The Megger MIT310A has a moving coil display for those who prefer a real moving needle. Black decals on a white background give high contrast, even in poor light conditions.

#### Tough:-

- Designed to take the bashing that testers receive on site, the Megger MIT insulation testers are rubber armoured.
- The rigid display cover folds right out of the way during testing and locks down to protect the display when it is finished.

#### Simple to use:-

- No buried functions mean it is obvious how to use the Megger MIT.
- Colour coded ranges help test selection, reducing testing time and help with fault location.
- A user guide in the lid provides all the basic information.

#### Hands free use:-

- It hangs comfortably around the neck for hands-free use because the instrument is carefully balanced.

- Continuity and buzzer testing starts automatically on connection to the circuit.
- Insulation tests being activated from the instrument or the switch probe, supplied with MIT320 and MIT330 (not suitable for the use with the MIT300 or MIT310).

#### Back lighting:-

- Both the display and the range selected can be read in the dark because the MIT 320/330 has a backlit display and range selection.

#### Safety features:-

To protect the user and the tester from incorrect use the MIT series all have an extensive range of features known as the Megger Intelligent Safety System including:

- Safety Interlock – prevents unsafe connection of test leads
- Safe contact detectors – Even if the MIT is connected to a live circuit whilst on continuity setting the tester will remain safe and not be damaged.
- Live voltage warning – alerts the operator when a circuit voltage over 25 V exists.
- Safety lockout – Prevents the test from operating when the circuit voltage is >50 V.
- Continuity check – prevents a continuity test or buzzer test on a live circuit.

The MIT300, 310, 320 and 330 meet or exceed the UK and International Wiring Regulations, including requirements

## MIT300 Series Insulation and Continuity Testers

of BS7671 and VDE 0413 parts 1 and 4, HD 384, IEC 364, NFC15-100, NEN3140, ES59009 and EN 61557.

In addition the range meets the requirements of IEC 61010-1 for safe connection to a 440 V Installation Category III supply (600 V Phase to Earth).

The MIT330 additionally offers the facility to save test results to internal memory. Over 1000 result can be saved on site, and downloaded to a computer when convenient. Data is stored in non-volatile memory, being retained when the instrument is switched off or batteries are exhausted.

A Job reference number can be selected for a range of results, allowing separate locations to be tested with the same tester and easily separated when downloaded.

A memory bar graph acts as a 'Fuel Gauge' showing how much memory has been used.

Test results are downloaded to CSV (Coma Separated Variable) spreadsheets, and can be imported into Microsoft Excel. If certificates or reports are required, the results can be downloaded directly into Megger Powersuite Professional with a range of features for creating professionally finished documentation.

### APPLICATION

The MIT300 series has applications in all aspects of domestic, commercial and industrial electrical contracting, building maintenance, testing, inspection and servicing.

Combining both Insulation testing and continuity testing, each instrument caters for all aspects of fixed wiring installations.

Further applications can be found in panel building, testing of motors, generators, switchgear and power tools, street lighting and low volume manufacturing environments etc.

All the MIT300 (except MIT310A) range is supplied with a full 3 years warranty.


### SPECIFICATIONS

#### INSULATION RANGES

##### Nominal Test Voltage

MIT310, 310A, 320, 330 1000 V, 500 V, 250 V (d.c.)  
MIT300 500 V, 250 V (d.c.)

#### Terminal Characteristics



#### MEASURING RANGE

**All instruments** 10 kΩ - 999 MΩ on all ranges

**Short Circuit Current** 1.5 mA nominal

**Test Current on Load** 1 mA at min. pass values of insulation (as specified in BS7671, HD 384 and IEC 364)

#### Accuracy (at 20 °C)

MIT300, 310, 320, 330 ±3%, ±2 digits up to 10 MΩ, ±5% up to 100 MΩ, ±30% up to full scale

MIT310A <2.5% of scale length (or 30% of reading 200 kΩ to 10 MΩ)

#### CONTINUITY RANGES

**Measuring Range:** 0,01 Ω - 99,9 Ω (0 -50 Ω on analogue scale)

**Open Circuit Voltage:** 5 V ±1 V

##### Short Circuit Current

MIT300, 310, 320, 330 205 mA +10 mA -5 mA

MIT310A 200 - 250 mA

#### Accuracy (at 20 °C)

MIT300, 310, 320,330 ±3% ±2 digits

MIT310A ±2.5% of scale length (or 30% of reading 0.2 Ω to 2 kΩ)

**Measuring range** 0 - 2 / 20 / 200 / 2 kΩ

**Open circuit voltage** 1.5 V +/-0.5 V

## MIT300 Series Insulation and Continuity Testers

### Zero Offset Adjust

MIT300, 310, 320, 330	0 - 9 $\Omega$
MIT310A	0 - 0.5 $\Omega$

### Continuity Buzzer

MIT300, 310	Operates at <5 $\Omega$
MIT320, 330	Adjustable 1 $\Omega$ to 20 $\Omega$
MIT310A	Operates at <5 $\Omega$
MIT300, 310, 320, 330	Response time <20 ms
MIT310A	Response time <100 ms

### Resistance range MIT320/330

(can be used for diode testing)

**Measuring Range:** 10  $\Omega$  - 1 M $\Omega$

**Open Circuit Voltage:** 5 V

**Short Circuit Current:** 1.5 mA

**Accuracy (at 20° C):**  $\pm 5\%$   $\pm 2$  digits up to 100 k $\Omega$

### Measuring Range (MIT310A)

0 - 2 k $\Omega$  (refer to continuity)

### Voltage range

**Measuring Range:** 0 - 600 V a.c. (50/60 Hz) or d.c.

### Accuracy (at 20 °C)

**MIT310, 320, 330** d.c. or a.c. (50/60 Hz):  
 $\pm 1\%$ ,  $\pm 2$  digits

**MIT310A**  $\pm 2.5\%$  of scale length for  
50/60 Hz

### Temperature coefficient:

<0,1% per °C on all ranges.

**Default voltmeter** all modes except off

**MIT310, 320, 330** >25 V a.c. or d.c. is applied display  
will operate as a voltmeter.

**MIT300** Beeps and flash 'V' on the display

**MIT310A** All modes including OFF

**Test inhibit:** If more than 50 volts is detected,  
testing will be inhibited.

### AutoPower Down (MIT310, 320, 330)

Auto power down operates after 10 minutes if left in  
standby mode.

### Temperature and humidity

**Operating Range:** -10 °C to +60 °C

**Operating Humidity:** 93% R.H. at +40 °C max.

**Storage Range:** -25 °C to +70 °C

### Test Result Storage (1000 results)

**Job Number** 255 locations

**Distribution Board no.** 99 locations

**Circuits** 99 locations

### Phases

P1, P2, P3

Last recorded result may be recalled to the display.

All data can be downloaded to a PC using Download  
Manager (supplied) or Megger Powersuite Professional of  
Windows software

**Communications** USB interface

### Environmental Protection:

IP54

### Fuses

Terminals 500 mA (F) 600 V, 32 x 6 mm Ceramic HBC 10  
kA minimum.

Display shows if fuse is ruptured.

### Safety

Meets the requirements of IEC61010-1 CAT III 600 V phase  
to earth.

### Automatic discharge

After an insulation test the item under test will be  
discharged automatically. Any voltage present will be  
indicated on the display so that the discharge can be  
monitored.

### Power supply

#### Battery:

8 x 1,5 V cells IEC LR6 type (AA alkaline).

Rechargeable NiCd or NiMH cells may be used.

Battery condition is constantly shown on the display as a  
four-section bargraph.

#### Battery Life

5000 consecutive tests (5 seconds per test) on any test  
using 2 Ah batteries.

#### Weight

**All units:** 980 gms

#### Dimensions

**All units:** 203 x 148 x 78 mm  
(8 x 5.7 x 3.2 inches)

#### E.M.C.

In accordance with IEC61326-1

## MIT300 Series Insulation and Continuity Testers

### MIT300 SERIES BENEFITS

	MIT300	MIT310	MIT310A Analogue	MIT320	MIT330
<b>Insulation testing</b>					
250 V	■	■	■	■	■
500 V	■	■	■	■	■
1000 V		■	■	■	■
Test range	999 MΩ	999 MΩ	999 MΩ	999 MΩ	999 MΩ
Insulation limit alarm (0.01 MΩ to 1 Ω)				■	■
<b>Continuity testing</b>					
Continuity to 100 Ω	■	■	■	■	■
Continuity buzzer	■	■	■	■	■
Lead null to 9 Ω	■	■	0.5 Ω	■	■
Adjustable buzzer 1 to 20 Ω				■	■
Audible buzzer disable				■	■
<b>Voltage measurement</b>					
Volts AC/DC		600 V	600 V	600 V	600 V
<b>Resistance measurement</b>					
10 Ω to 1 MΩ range				■	
<b>Features</b>					
Voltage warning	■				
Default voltmeter		■	■	■	■
Backlit display				■	■
Backlight selector ranges				■	■
Locking test button	■	■	■	■	■
Auto powerdown	■	■		■	■
Switched test probe				■	■
IP54 weatherproof	■	■	■	■	■
Accepts rechargeable batteries	■	■	■	■	■
1000 Test result storage					■
Downloading					■
Calibration certificate	■	■		■	■
3 years warranty	■	■		■	■

### ORDERING INFORMATION

Description	Part number	Description	Part number
<b>Product</b>		<b>Optional accessories</b>	
MIT300 250 V, 500 V insulation tester	MIT300-EN	Fused test lead set	1002-015
MIT310 250 V, 500 V, 1000 V insulation tester	MIT310-EN		
MIT310A 250 V, 500 V, 1000 V analogue insulation tester	MIT310A-EN		
MIT320 250 V, 500 V, 1000 V insulation tester	MIT320-EN		
MIT330 250 V, 500 V, 1000 V insulation tester	MIT330-EN		
<b>Included accessories</b>			
Test lead set and crocodile clips	1002-001		
SP4F Switch probe (MIT320 and MIT330 only)	1007-156		

#### SALES OFFICE

Megger Limited  
Archcliffe Road Dover  
CT17 9EN England  
T +44 (0) 1304 502101  
E UKsales@megger.com

#### MIT300\_DS\_en\_V16

www.megger.com  
ISO 9001

The word 'Megger' is a registered trademark

**Megger**<sup>®</sup>