

FEATURES

- Material: UL approved Nylon 66, 94V-2
- Color: Grey (RAL7001)available in other colors.
- Suit a variety of applications, and diverse industries.
- Function :Mount gland to pre-drilled panel hole, use locknut to fix gland on board, insert the cables in the seal,and then tighten up the nut to hold cables in position.
- Simply and quickly fixed, high degree of the protection IP68 preventing dust and water.

RS PRO Cable Gland

RS Stock No.: 214-1072



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

- Material: UL approved Nylon 66, 94V-2
- · Color: Grey(RAL7001), available in other colors.
- · Suit a variety of applications, and diverse industries.
- Function: Mount gland to pre-drilled panel hole, use locknut to fix gland on board, insert the cables in the seal, and then tighten up the nut to hold cables in position.
- Feature: Simply and quickly fixed, high degree of the protection IP68 preventing dust and water.
- Available to order the accessories separately. Follow the drawing and add the letter to the suffix part number, L for locknut, W for washer, B for gland body, S for seal, N for nut.

General Specifications

Series	Metric Thread
Туре	Cable Gland
Colour	Grey(RAL7001)
Material	Nylon 66
Finish	
Application	
Resistant To	
UV Resistant	No
Minimum Operating Temperature	-40°C
Maximum Operating Temperature	85°C
Fire Behaviour	Self-Extinguishing
Quantity	5pcs

Mechanical Specifications

Thread	M40 x P1.5
Mounting Hole	40.0~40.4 mm
Cable Range	20 ~ 28 mm



Protection Category

IP Rating	IP68
1	

Approvals

Declarations	
Standards Met	UL, RoHS, CE, IP68, HF

Similar Products

Stock No.	Brand	Product Name	Colour	Material	Thread
669-4689	RS PRO	Cable Gland	Black	Nylon 66	M40 x P1.5
669-4670	RS PRO	Cable Gland	Black	Nylon 66	M32 x P1.5











RS Article	Thread	Mounting Hole	D1	D2	B1	L1	L2	L3	Cable Range	Packing
2141072	M40xP1.5	40.0~40.4	40	32.7	28.2	10	39.4	27.5	20 ~ 28	5PCS

