



Main

Range	ComPact
Range of product	ComPact NSXm new generation
Device short name	MN
Product or component type	Voltage release
Device application	Control
Voltage release type	Opening coil Undervoltage release
[Uc] control circuit voltage	220...240 V AC 50 Hz 208...240 V AC 60 Hz
Range compatibility	ComPact ComPact NSXm new generation ComPact ComPact NSXm PowerPact PowerPact B

Complementary

Operating threshold	0.35...0.7 x Un opening 0.85 x Un closing
Response time	< 50 ms
Auxiliary connection terminal	Pre-wired 0...0.8 mm ² (AWG 18)stranded copper
Wire stripping length	8 mm
Cable length	1 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	6 cm
Package 1 Length	8.5 cm
Package 1 Weight	83 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9 cm
Package 2 Width	13 cm
Package 2 Length	18.5 cm
Package 2 Weight	880 g
Unit Type of Package 3	S03
Number of Units in Package 3	120
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	10.9 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins