

Datasheet

RS Pro Non-Fused Terminal Block, 12 Way/Pole, Screw Terminals, 25 mm², PP, 500 V

RS Stock No: **868-0742**



Product Details

RS Pro non-fused terminal block with 12 ways, has natural polypropylene housing. This terminal block with 25-mm² wire, features screw termination. The panel mount block with brass contact, has a voltage rating of 500 V.

Features and Benefits

- Self-extinguishing of UL-94 V-2, IEC 695-2-1 to 850°C, IEC 695-2-2
- galvanised steel screws
- Maximum continuous ambient temperature of 85°C
- Meets UL-94 V-2; IEC 695-2-1 to 850°C and IEC 695-2-2, EN 60998-1: 2004, EN 60998-2-1: 2004, EN 60335-1: 2002 + A2: 2006 (S.C. 30.2.3) and IEC/EN 60695-2-11 standards



ENGLISH

Specifications:

Contact Material	Brass
Enclosed	No
Material	Polypropylene Housing
Maximum Operating Temperature	+85°C
Mounting Type	Panel Mount
Number of Ways	12
Pitch	19.5 mm
Termination Method	Screw
Voltage Rating	500 V
Wire Size	25 mm ²
Colour	Natural
Standards Met	RoHS, UL 94V-2; IEC 695-2-1, IEC 695-2-2, EN 60998-1:2004, EN 60998-2-1:2004, EN 60335-1:2002 + A2:2006 (S.C. 30.2.3), IEC/EN 60695-2-11