
multicomp PRO

RoHS Compliant

Diagram



0.1M to 0.5M, T=15mm 0.5M to 1M, T=25mm 1M to 2M, T=30mm 2M to 5M, T=50mm

| Wire Style Number: UL1015 Rated Temperature: 105°C Rated Voltage: 600V Material of Insulation: PVC / Yellow / Green | | | | | | | | | | |
|------------------------------------------------------------------------------------------------------------------------------|-----------|--------------|---------|----------|-------------------------------------|--|--|--|--|--|
| Part Number | Conductor | | | | | | | | | |
| | AWG-No. | Construction | CON.DIA | Diameter | Conductor Resistance 20°C (Ω/KM) | | | | | |
| MP010795 | | 41/0.254 | 1.88 | 3.5 | | | | | | |
| MP010796 | 14 | | | | 8.62 | | | | | |
| MP010797 | 14 | | | | | | | | | |
| MP010798 | | | | | | | | | | |
| MP010799 | | 65/0.254 | 2.37 | 3.9 | | | | | | |
| MP010800 | 10 | | | | E 40 | | | | | |
| MP010801 | 12 | | | | 5.43 | | | | | |
| MP010802 | | | | | | | | | | |


Dimensions : Millimetres

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

Conductor



multicomp PRO



Material: Copper Plating: Tin

| Wire Range | Part Number | Stud Size | | Dimension | | |
|------------------------|-------------|-----------|-----|-----------|------|-----|
| mm²/AWG | Fart Number | Stud | d2 | w | L | Т |
| 1.5-2.5mm² 16-14AWG | MP010795 | #4 | 3.2 | | 13 | 0.8 |
| | MP010796 | #6 | 3.7 | 6.6 | | |
| | MP010797 | #8 | 4.3 | | 14.5 | |
| | MP010798 | #10 | 5.3 | 8.5 | 16.8 | |
| 4-6mm² 10-12AWG | MP010799 | #4 | 3.2 | | 16.2 | 1 |
| | MP010800 | #6 | 3.7 | 7.2 | | |
| | MP010801 | #8 | 4.3 | | | |
| | MP010802 | #10 | 5.3 | 9.5 | 19.8 | |

Dimensions : Millimetres

Tolerance: ±0.3mm

Part Number Table

| Description | Part Number | |
|------------------------------------------------|-------------|--|
| Ground Cable, 14AWG, 3.2mm Ring Terminal, 0.3m | MP010795 | |
| Ground Cable, 14AWG, 3.7mm Ring Terminal, 0.3m | MP010796 | |
| Ground Cable, 14AWG, 4.3mm Ring Terminal, 0.3m | MP010797 | |
| Ground Cable, 14AWG, 5.3mm Ring Terminal, 0.3m | MP010798 | |
| Ground Cable, 12AWG, 3.2mm Ring Terminal, 0.3m | MP010799 | |
| Ground Cable, 12AWG, 3.7mm Ring Terminal, 0.3m | MP010800 | |
| Ground Cable, 12AWG, 4.3mm Ring Terminal, 0.3m | MP010801 | |
| Ground Cable, 12AWG, 5.3mm Ring Terminal, 0.3m | MP010802 | |

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

