




CABLE ASSEMBLIES



Cable Assemblies

Part No. 123680/Termination-Termination/Cable Length/Colour
Example :

123680/OS-FS/1.2/Black = Shutter Plug to Fixed Shroud Plug. 1.2 metre long, Black.

Cable = 1mm² double insulated silicone 3.6mm Ø.
Multistranded very flexible copper core. 7/36/0.071
Standard lead length = 1.2 metre. Other lengths available.

Part No 134328


Extension Lead.

On some occasions the need for a lead longer than the standard length is required. This reel holds just over 12 mtrs (40 foot) of the highly flexible double skinned silicone cable as used on

the standard lead assemblies.

One end of the lead is terminated in a 4mm right angled plug, the other has a 4mm socket into which the original lead can be plugged.

Designed to be robust and sturdy.



Part No TLR 50M

50 Metre Test Lead Reel

**IDEAL FOR EARTH CONTINUITY TESTING
AND ANY OTHER EXTENDED TESTING
SCENARIO.**

This robust purpose made cable reel contains 50 metres of our high quality double insulated silicone cable. The reel incorporates a 4mm socket and the cable is terminated in a 4mm right angle plug.

Other cable colours available upon request



Silvertronic Limited.

Stockingswater Lane. Enfield. Middlesex. EN3 7PH England.

Tel : 44 (0)208 805 3424 Fax : 44 (0)208 805 3054

e-mail : sales@silvertronic.com

North American Office:

Silvertronic Inc.

620 East Smith Road. Unit W-19. Medina. Ohio 44256. U.S.A

Tel : Toll Free 866 556 3308 Fax : 330 722 2281

e-mail : ussales@silvertronic.com

Home :: About us :: Catalogue :: Contact us

Copyright© Silvertronic Ltd. 2003. All rights reserved.