



Main

| | |
|---------------------------|--------------------|
| Range | Vivace |
| Product or component type | Switch |
| Device short name | KB31 |
| Device application | Control |
| Device presentation | Complete mechanism |

Complementary

| | |
|--------------------------------|---------------------------------------------------------------------|
| Switch function | 2-way |
| Actuator | Rocker |
| Pilot light | Neon indicator lamp |
| Number of gangs | 1 gang |
| Colour tint | Aluminium silver |
| Material | Polycarbonate: grid plate Polycarbonate: surround Nylon: base |
| Projecting depth | 8 mm |
| Device mounting | Flush |
| Mounting support | Wall mounted |
| Fixing mode | By screw M3.5 |
| Fixing center | 60.3 mm |
| Embedding depth | 35 mm |
| Rated current | 20 A at 250 V AC, inductive 20 A at 250 V AC, resistive |
| [Ue] rated operational voltage | 250 V AC |
| Network frequency | 50 Hz |
| Contacts material | Brass and phosphor bronze |
| Connections - terminals | Pillar terminal |
| Terminal identifier | L2 N2 L1 N1 |
| Tightening torque | 0.4 N.m |
| Clamping connection capacity | $\leq 2.5 \text{ mm}^2$ |
| Width | 86 mm |
| Height | 86 mm |

Environment

| | |
|---------------------------------------|-----------------------------------------|
| Standards | SS 227 IEC 60669-1 MS IEC 60669-1 |
| Ambient air temperature for operation | -5...40 °C |
| Relative humidity | 0...95 % |
| Environmental characteristic | Indoor use |