

FEATURES

- High pressures and high flow rates
- High quality gaskets
- Class H coils
- Products traceability

RS PRO Pneumatic Solenoid Valves

RS Stock No.: 2554171



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The RS Pro Solenoid valve has simple and compact design, the fluidity solenoid valves are available in 3/2NC versions. The materials used allow the FLUIDITY solenoid valves to be installed also in food applications or in contact with aggressive fluids and reach working temperatures from -40°C to +180°C. The proposed coils allow to obtain high performances and on request low power consumption.

General Specifications

Materials

| | |
|----------------------|-------|
| Body/Sub-Base | Brass |
|----------------------|-------|

Electrical Specifications

| | |
|-----------------------|------|
| Supply Voltage | 24 V |
|-----------------------|------|

Mechanical Specifications

| | |
|------------------------|--------------|
| Number of Ports | 2/2 NC |
| Connection | 3/4 G female |
| Connection Size | 3/4 in |
| Operation | Solenoid |

Operation Environment Specifications

| | |
|--------------------------------------|----------------|
| Operating Temperature Range | -10°C to +80°C |
| Minimum Operating Temperature | -20°C |
| Maximum Operating Temperature | 40°C |

Approvals

| | |
|----------------------|--|
| Standards Met | EN1127, EN80079-36, EN80079-37 |
| Declarations | EU Declaration of Conformity, UE Declaration of Conformity |

**CONSTRUCTIONAL/SCHEMATIC DIAGRAMS /ACCESSORIES
WITH PRODUCT**