



Data Sheet

ENGLISH

57mm 1.8' HIGH TORQUE STEPPER 200 STEP

RS stock number 535-0423






Dimensions in mm

| Specifications | |
|--|----------|
| Model | 535-0423 |
| Step Angle | 1.8° |
| Step Angle Accuracy (Full Step, No Load) (%) | ±5% |
| Rated Voltage (V) | 2.3 |
| Current/ Phase (A) | 2.8 |
| Resistance/Phase (Ω) | 0.83 |
| Inductance/Phase (mH) | 2.2 |
| Detent Torque (mNm) | 35 |
| Holding Torque (Ncm) | 101 |
| Rotor Inertia (g-cm²) | 275 |
| Weight (Kg) | 0.65 |
| Number Of Leads (No.) | 4 |

Speed V Torque Characteristics



| Characteristics | |
|---|--|
| Resistance Accuracy ±10% | |
| Inductance Accuracy ±20% | |
| Temperature Rise 80°C Max. (Rated Current 2 phase On) | |
| Ambient Temp -20 °C to +50 °C | |
| Insulation Resistance 100mm Ωmin.,500Vdc | |
| Dielectric Strength 500Vac for 1 min | |
| Shaft Radial Play 0.06mm Max. (450G-Load) | |
| Shaft Axial Play 0.08mm Max. (450G-load) | |
| | |
| | |

