Pushbutton Switch Sub-Miniature, Sealed

multicomp PRO



Diagram

.032 [0.80]

Specifications

Material

Case Plunger Bushing Movable Contact Terminal

Electrical

Rating Contact Resistance Insulation Resistance Dielectric withstanding voltage Life

Temperature Rating Operating temperature

Environmental Sealed Rated

 \oplus

RECOMMENDED PCB LAYOUT : IP67

: 20mΩ max.

: 1000MΩ min.

: -30°C to +85°C

: PA9T, Rated UL94V-0, Colour Red

: Copper Alloy, Gold Over Nickel under plate

: Copper Alloy, Gold Over Nickel under plate


: FR52, Rated UL94V-0

: PA9T, Rated UL94V-0

: 0.4A max. @ 20V AC or DC

: 1500V RMS @ sea level

: 30,000 cycles at full load



BUTTON POSITION		
FUNCTION	ON	мом
TERMINALS	2-1	2-3

Dimensions : Millimetres

Part Number Table

Description	Part Number
Pushbutton Switch, SPDT, On-MOM, R/A, PCB Tails	MP-PB9-AAB00A2RE-6

CIRCUIT DIAGRAM

(SPDT)

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro



RoHS Compliant