83154

PratiKa industrial socket - 16 A - 2P + E - 200...250 V AC - IP67





| Main | |
|---------------------------|----------------|
| Range | PratiKa |
| Product or component type | Socket |
| Device short name | PratiKa socket |
| Plug, socket category | Low voltage |
| Poles description | 2P + E |
| Network type | AC |
| Outlet standard | Industrial |

Complementary

| o o mpromornamy | | |
|-------------------------------------|---|--|
| Mounting mode | Wall-mounted | |
| Plug, socket, control station shape | Angled | |
| [In] rated current | 16 A | |
| [Ue] rated operational voltage | 200250 V | |
| Network frequency | 50/60 Hz | |
| Ground lug clockwise position | 6 h | |
| Plug, socket material | Housing: self-extinguishing engineering polymer | |
| Contacts material | Pins: stainless steel Sleeves: nickel plated brass Springs: stainless steel | |
| Connections - terminals | Captive screws, completely loosened | |
| Cable cross section | 14 mm² | |
| Cable outer diameter | 815 mm | |
| Cable entry | Cable gland | |
| Thread type | Pg 16 | |
| Net weight | 0.324 kg | |
| Base dimension | 80 x 100 mm | |
| Height | 155 mm | |
| Width | 80 mm | |
| Depth | 126 mm | |
| Colour | Grey (RAL 7035) | |
| Voltage colour | Blue | |

Environment

| Standards | EN 60309-2 | |
|---------------------------------------|-------------------------------------|--|
| | EN 60309-1 | |
| IP degree of protection | IP67 conforming to IEC 60529 | |
| IK degree of protection | IK08 conforming to EN 62262 | |
| Fire resistance | 850 °C conforming to IEC 60695-2-11 | |
| Relative humidity | 50 % at 40 °C | |
| | 70 % at 30 °C | |
| | 90 % at 20 °C | |
| Ambient air temperature for operation | 35 °C (86400 s) | |

Packing Units

| Unit Type of Package 1 | PCE |
|------------------------------|----------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 12.5 cm |
| Package 1 Width | 8.0 cm |
| Package 1 Length | 15.0 cm |
| Package 1 Weight | 278.0 g |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 4 |
| Package 2 Height | 17.0 cm |
| Package 2 Width | 26.0 cm |
| Package 2 Length | 27.0 cm |
| Package 2 Weight | 1.294 kg |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 8 |
| Package 3 Height | 30.0 cm |
| Package 3 Width | 30.0 cm |
| Package 3 Length | 40.0 cm |
| Package 3 Weight | 3.075 kg |
| | |

Offer Sustainability

| Green Premium product |
|---|
| REACh Declaration |
| Compliant EPEU RoHS Declaration |
| Yes |
| China RoHS Declaration |
| ₽¥Yes |
| Product Environmental Profile |
| The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| |

Contractual warranty

| Warranty | 18 months |
|----------|-----------|
| | |