Surface Mount Resistor




Current Sense

FEATURES

- Thin Film
- 2512 Package
- TCR ±100 PPM / °C
- Tolerance 0.5%
- Power rating 3W
- Ω = R100

RS PRO Chip Resistor

RS Stock No.: 2414955



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Surface Mount Resistor



Product Description

A series of Thin Film surface mount Current sense chip resistors. Packages that include 0603, 0805, 1206, 2010 and 2512 covers power ratings ranging from 0.1W to 3W measured at 70°C Current sense resistors can also be referred to as shunt resistors. The resistors have very low resistance enabling them to minimise power consumption which in turn helps eliminate any risk of component / equipment damaging short circuits. They detect and convert current to a measured output voltage.

Applications that include over current protection for audio, DC DC converters, Voltage regulation modules, charging modules, battery packs and adaptors.

General Specifications	
Substrate material	High Purity Alumina

Mechanical Specifications	
Packaging	Plastic Reel / Reel 4000
Electrical Specifications	
Operating Temp range	-55 to 155°C
Protection Category	
Classification	
eCI@ss (Version)	
UNSPSC (Version)	
Approvals	
Declarations	MFR Declaration of Conformity
Hazardous Area Certification	

Surface Mount Resistor

Standards Met

Similar Products

Stock No.	Brand	Product Name	Ohmic value	Package	Power Rating
2414957	RS PRO	Current sense	R100	2512	3W
XXX-XXX	RS PRO				

Connection Diagrams / Assembly Diagrams / Illustrations / Accessories