




0	Creation	BLONDEL N.	11.05.2006	DP 11.05.2006
Ind.	Object	Drawn :	Date :	Checked : Date :
TYPE J LEAF E06010		N° 621-2237		
		Material :	Scale :	
		-	N.T.S	
		unless otherwise specified Generale tolerances ± 0.1 mm		
		94-05-08-TE-079 Rév.2		



4	Heat shrink	PE
3	Sleeve	PE
2	cable	FG/S.SBraid
1	Leaf	AISI 304L
Tag	Description	Material

0	Creation	BLONDEL N.	11.05.2006	DP	11.05.2006
Ind.	Object	Drawn :	Date :	Checked :	Date :

TYPE J LEAF E06010	N° 621-2237
-----------------------	--------------------

	Material : -	Scale : N.T.S
	<small>unless otherwise specified Generale tolerance: ± 0.1 mm</small>	 <small>94-05-08-TE-079 Rév.2</small>

Description

Type J Leaf

Thermocouple type

J

Grounded or Ungrounded

Grounded

According to IEC-BS 4937 60584-2 & IEC-BS 4937 60584-3

RoHS compliance

Yes

Accuracy Class 2

±2.5°C or ±0.0075xT

Colour Codes IEC 60584

+VE arm	black
-VE arm	white
overall	black

Temperature

Range	-50 to +750° C
Operating	-50 to +400° C

Cable characteristics

Section	7x0.2
Conductor Insulation	0.22 mm²
Braid	Glass fiber
Length	StainlessSteel
	2000 mm

Leaf dimensions



25 x 13x 0.15

Connection

On side of the leaf

Application

contact temperature

0	Creation	BLONDEL N.	11.05.06	DP	11.05.06
Ind.	Object	Drawn :	Date :	Checked :	Date :
TYPE J LEAF			N° 621-2237		
E06010					
			Material :		Scale :
					N.T.S
			Unless otherwise specified generales tolerances ± 0,1mm		
					<small>94-05-08-TE-079 Rév.2</small>