

Dual Channel PC Based Oscilloscope

multicomp PRO



Features

- Up to 100MHz bandwidth, and max. 1GS/s real-time sample rate
- 2 Channels
- Max 10M record length
- Friendly UI : FFT, or X-Y, and waveform 2 views displayed on the same screen
- Multi-trigger option: edge, video, slope, pulse, and alternate
- USB isolation - less signal interference, more PC protection
- USB bus powering, and LAN remote control (optional)
- Ultra-thin body design, easy portability
- SCPI supported
- LabVIEW supported (only in MP720019 EU-UK)

Oscilloscope Specifications

Parameters	MP720017 EU-UK	MP720016 EU-UK	MP720018 EU-UK	MP720019 EU-UK
Bandwidth	25MHz		60MHz	100MHz
Channel	2 Analogue, 1 Ext Trigger			
Sample Rate	100MSa/s		1GSa/s	
Horizontal Scale (s/div)	5ns/div ~ 100s/div, step by 1~2~5			2ns/div ~ 100s/div, step by 1~2~5
Rise Time	≤14 ns		≤5.8 ns	≤3.5 ns
Record Length	5K		10M	
Input Coupling	DC, AC, GND			
Input Impedance	1MΩ±2%, in parallel with 10pF ±5pF			
Channels Isolation	50Hz : 100 : 1, 10MHz : 40 : 1			
Max Input Voltage	400V (PK - PK) (DC+AC, PK - PK)		40V (PK - PK) (DC+AC, PK - PK)	
DC Gain Accuracy	±3%			
DC Accuracy	Average≥16: ±(3% reading + 0.05div) for ΔT			
Probe Attenuation Factor	1X, 10X, 100X, 1000X			
LF Respond (AC, -3dB)	≥5Hz (at input, AC coupling, -3dB)			
Sampling Rate / Relay Time Accuracy	150ps			
Interpolation	sin(x) / x			

Newark.com/exclusive-brands
Farnell.com/exclusive-brands
Element14.com/exclusive-brands

multicomp PRO

Dual Channel PC Based Oscilloscope

multicomp PRO

Parameters		MP720017 EU-UK	MP720016 EU-UK	MP720018 EU-UK	MP720019 EU-UK
Interval (ΔT) Accuracy (full bandwidth)		Single: $\pm (1 \text{ interval time} + 100\text{ppm} \times \text{reading} + 0.6\text{ns})$, Average >16: $\pm (1 \text{ interval time} + 100\text{ppm} \times \text{reading} + 0.4\text{ns})$			
Vertical Resolution (A/D)		8 bits (2 channels simultaneously)			
Vertical Sensitivity		5mV/div ~ 5V/div			
Trigger Type		Edge, Pulse, Video, Slope, and Alternate			
Trigger Mode		Auto, Normal, and Single			
Trigger Level		± 5 divisions from screen center			
Acquisition Mode		Sample, Peak Detect, and Average			
Line / Field Frequency (video)		NTSC, PAL, and SECAM standard			
Cursor Measurement		ΔV , and ΔT between cursors			
Automatic Measurement		Vpp, Vmax, Vmin, Vtop, Vbase, Vamp, Vavg, Vrms, Overshoot, Preshoot, Freq, Period, Rise Time, Fall Time, Delay A→B ↗, Delay A→B ↘, +Width, -Width, +Duty, -Duty			
Waveform Math		+, -, ×, ÷, invert, FFT			
Lissajous Figure	Bandwidth	Full bandwidth			
	Phase Difference	± 3 degrees			
Communication Interface		USB 2.0 (isolation)	USB 2.0	USB 2.0, LAN (optional)	
Multi-function Interface	Signal Type	Synchronized input / output, Pass / Fail, external trigger input			
	Level Standard	TTL			
Power Supply		5.0V/1A			
Power Consumption		$\leq 1.5\text{W}$		$\leq 5\text{W}$	
Dimensions (W × H × D)		170mm × 120mm × 18mm		190mm × 120mm × 18mm	
Device Weight		0.26 kg			0.3 kg
Standard Accessories Included		USB Cable, CD-Rom, Manual, Probes, Probe Adjust Tool			
Optional Accessories		Soft bag			
Warranty		12 months			

Part Number Table

Description	Part Number
Dual Channel PC Based Oscilloscope, 25MHz	MP720016 EU-UK
Dual Channel PC Based Oscilloscope, 25MHz	MP720017 EU-UK
Dual Channel PC Based Oscilloscope, 60MHz	MP720018 EU-UK
Dual Channel PC Based Oscilloscope, 100MHz	MP720019 EU-UK

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands
Farnell.com/exclusive-brands
Element14.com/exclusive-brands

multicomp PRO