
# Datasheet

RS Stock No. 1856071







Cable entry set, IP66, Consisting of: 1 x KDS-SR 10/24, 1 each of KDS-Inlay 1,2,4,6

**RAL:** 9005

#### **Business data**

Abez 3 - product description	Cable Entry
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	87.9
Weight per piece (including packaging)	111.9
Unit of weight	G
Customs number	39259020
Country of origin	DE

RS PRO

**Technical Data** 

Dimensions		
Length	153 mm	
Lenght of wall cutout	113,5 mm	
Width	70 mm	
Width of wall cutout	46 mm	
Height	19.6 mm	
Installation height	19.6 mm	
Diameter of the screw holes	5.5 mm	
Materials		
Material	Polyamide 6.6	
Glass-fibre reinforced	$\checkmark$	
Flammability class UL 94	V-0	
Working temperature, min.	-40 °C	
Working temperature, max.	120 °C	
Sealing material	Polyurethane-based	
Type of seal	Sealing and moulded flexible foam	
Halogen-free	$\checkmark$	
Silicone-free	$\checkmark$	



**Technical Data** 

Further technical data			
Mounting type	Screws		
Protection	IP66		
NEMA Type	4x		
Number of screw holes	4		
Fixing screws	M 5 (ISO 4762 / DIN 912)		
Torque of the fixing screws	3 Nm		



Approvals

cUL approval				
cUL approval	C22.2 No. 14-95			
cUL approval granted	$\checkmark$			
UL approval				
UL approval	UL 508			
UL approval granted	V			

Media



