



CARBOPRESS N/L 10

Suitable for fuel oils, petrol and diesel having an aromatic content not exceeded 50 % and also for grease.

Hose Construction

Tube: Black, smooth, NBR rubber compound
Reinforcement: Synthetic textile yarns
Cover: Black, smooth, abrasion, oil, fuel, and weather-resistant, antistatic (R < 1 MΩ/m) special NBR rubber compound

Temperature Range

-25 °C (-13 °F) to +80 °C (+176 °F)
 up to +100 °C (+212 °F) for oil








- Also suitable for water and air in general service applications
- Design Factor 3:1
- B100 compatible

Tolerances

According to UNI EN ISO 1307
 Refer to Technical Handbook on page TH34

Fitting Series

64 + 47
 56

Part Number							
	I.D. (mm)	O.D. (mm)	MPa	psi	bar		
CARBOPRESS N/L 10							
IH30501001/100	5	12	1.0	150.0	10	0.12	40
IH30511003/100	6	12	1.0	150.0	10	0.11	50
IH30511002/100	6	13	1.0	150.0	10	0.14	50
IH30501002/100	8	15	1.0	150.0	10	0.17	65
IH30501003/100	10	17	1.0	150.0	10	0.20	80
IH30501004/100	13	20	1.0	150.0	10	0.24	105
IH30511004/100	16	23	1.0	150.0	10	0.29	130
IH30501006/40	19	27	1.0	150.0	10	0.39	150
IH30501007/50	25	35	1.0	150.0	10	0.63	200

Hose layline example

RUBBER HOSE CARBOPRESS W.P. bar

