

FEATURES

- Made of polyamide, in green
- Dimensions of 5.08 mm (L) x 6.2 mm (D)
- Pitch of 2.54 mm
- 2 contacts
- Single row
- Through hole mounting
- Female
- Straight body orientation
- Screw type termination method
- Current rating of 6 A
- Voltage rating of 125 V
- Operating temperature range of -40°C and +105°C

RS PRO 2.54mm Pitch, 2 Way PCB Terminal Strip

RS Stock No.: 790-1098



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Link wires quickly and efficiently across separate PCBs with this 2-way PCB (printed circuit board) terminal strip. This modular, insulated device can be directly mounted on your PCB.

General Specifications

Number Of Contact	2
Number Of Rows	1
Mounting Type	Through Hole
Gender	Female
Termination Method	Screw
Type	PCB Terminal Block
Body Orientation	Straight
Colour	Green
Material	Polyamide
Flammability Rating	UL 94 V-0
Applications	PCB

Electrical Specifications

Current Rating	6A
Voltage Rating	125V
Insulation Resistance	>2000M Ω
Insulation Withstand Voltage	2000V ac

Mechanical Specifications

Pitch	2.54mm
Depth	6.2mm
Width	5.54mm
Length	5.08mm

Operation Environment Specifications

Operating Temperature Range	-40°C to 105°C
-----------------------------	----------------

Approvals

Compliance/Certifications	EN61340
---------------------------	---------



