



Main

Range of product	ZENcolo
Product or component type	Power socket-outlet
Switch function	1-pole
Rated current	13 A at 250 V AC 50 Hz
Cover frame colour tint	Silver satin
Cover plate colour tint	Grey

Complementary

Device mounting	Flush Surface
Number of gangs	1 gang
Material	Polycarbonate grid plate Polycarbonate surround Brass contact plate Phosphor contact plate Polycarbonate base
Load type	Resistive
Connections - terminals	Folded terminal
Width	87 mm
Height	87 mm
Depth	8 mm

Environment

Relative humidity	0...95 %
Environmental characteristic	UV resistant indoor use
Operating altitude	2000 m
Standards	MS 589 SS 145 BS 1363-2

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.0 cm
Package 1 Width	8.72 cm
Package 1 Length	8.72 cm
Package 1 Weight	125.88 g

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Circularity Profile	End Of Life Information