



Benefits

- Excellent LED Illumination with glamorous classic shapes
- Emit light at an unobstructed and panoramic angle
- Create a well lit and cosy space
- Bright and comfortable

Application



Model	Item Description	W	PF	lm	lm/w	CRI	BA	Beam Angle	Single Box (LxWxH)mm	Outer Box (LxWxH)mm	Packing Qty (PCS/CTN)
LG7106v1-E27	BULB A60 6W E27 MK 4000K	6.0	0.5	470	78	80	240°	15000	59*59*109	378*315*235	60
A60S1-9.6W-F-E27	CLSV1 A60 9.6W E27 FS 3000K	9.6	0.5	1055	110	80	240°	20000	59*59*109	378*315*235	60
A60S1-9.6W-F-E27	CLSV1 A60 9.6W E27 FS 4000K	9.6	0.5	1100	114	80	240°	20000	59*59*109	378*315*235	60
A60S1-9.6W-F-E27	CLSV1 A60 9.6W E27 FS 6500K	9.6	0.5	1100	114	80	240°	20000	59*59*109	378*315*235	60

Application Conditions	
IP	IP20
Operating Temperature	-20~40°C
Application Temperature	25°C
Storage Environment	-25~50°C

Mechanical Properties	
Optical Material	PC
Housing Material	PBT
Finishing Colour	White

Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	220-240
AC/DC	AC

Dimensional Drawing

