# THE WORLD LEADER IN LADDERS



#### STYLE: Steel Step Stool with Tool Trav

Comfortable hand grip

Tray holds paint cans and tools to increase productivity



Comfortable tubular stiles

Oversize. slip-resistant steps with safety latch

Model 223T-6A7

· Lightweight, easy to use and store.

Large, non-marking feet

#### SPECIFICATIONS

| M10SKU | Model No. | Platform<br>Height | Stile Length | Approx.<br>Width | Approx.<br>Spread | Approx<br>Shipping Wt. |
|--------|-----------|--------------------|--------------|------------------|-------------------|------------------------|
| 184935 | 223T-6AZ  | 0.71m              | 0.76m        | 0.46m            | 0.65m             | 6.5kg                  |

#### **DIMENSIONS**

Open: 47cm wide, 65cm spread, 1.18m tall

Closed: 47cm wide, 6cm spread, 1.28m tall

## 22-6AZMODEL

LOAD RATING

DOMESTIC DIITY RATING

#### STYLE: Steel Step Stool

Comfortable hand grip

Comfortable tubular stiles



Oversize, slip-resistant steps with safety latch

Model 222-6AZ

Large, non-marking feet

· Lightweight, easy to use and store.

#### **SPECIFICATIONS**

|   |        |           | Platform | Stile  | Approx. | Approx. | Approx       |
|---|--------|-----------|----------|--------|---------|---------|--------------|
| ı | M10SKU | Model No. | Height   | Length | Width   | Spread  | Shipping Wt. |
| ı | 184933 | 222-6AZ   | 0.51m    | 0.56m  | 0.47m   | 0.53m   | 4.5kg        |

#### DIMENSIONS

Closed: 47cm wide, 7cm spread, 94cm tall Open: 47cm wide, 53cm spread, 87cm tall

## STYLE: Steel Step Stool

Comfortable hand grip



Oversize, slip-resistant steps with safety latch

Comfortable tubular stiles

Model 223-6A7

• Lightweight, easy to use and store.

Large, non-marking feet

#### SPECIFICATIONS

| M10SKU | Model No. | Platform<br>Height | Stile<br>Length | Approx.<br>Width | Approx.<br>Spread | Approx<br>Shipping Wt. |
|--------|-----------|--------------------|-----------------|------------------|-------------------|------------------------|
| 184934 | 223-6AZ   | 0.71m              | 0.76m           | 0.47m            | 0.65m             | 5.9kg                  |

#### **DIMENSIONS**

Open: 47cm wide, 65cm spread, 1.09m tall Closed: 47cm wide, 6cm spread, 1.18m tall

## 150BAZMODEL

135kg LOAD RATING

**INDUSTRIAL** DUTY RATING

## STYLE: Aluminium Step Stool



· Ideal for industrial, office and home applications

#### **SPECIFICATIONS**

| M10SKU | Model No. | Size | Approx.<br>Width | Approx.<br>Spread | Approx. Volume<br>per Unit | Approx<br>Shipping Wt. |
|--------|-----------|------|------------------|-------------------|----------------------------|------------------------|
| 184920 | 150BAZ    | 0.6m | 0.43m            | 0.48m             | 0.05m <sup>3</sup>         | 2.5kg                  |

| Top: 15cm x 32cm       | Treads: 8cm wide         | Front Flange: 2.25cm wide |
|------------------------|--------------------------|---------------------------|
| Front Stiles: 8cm wide | Rear Stiles: 2.75cm wide | Rear Flange: 2.5cm wide   |

## STYLE: Aluminium Dual Purpose 2 in 1 Ladder



#### Model DP366A7

• Versatile design - two ladders in one. Easily converts from a stepladder to a straight ladder.

#### SPECIFICATIONS

| M10SKU | Model No. | Size      | Max. Reach<br>Height* | Approx.<br>Width | Approx. Vol<br>per Unit | Approx<br>Shipping Wt. |
|--------|-----------|-----------|-----------------------|------------------|-------------------------|------------------------|
| 184922 | DP366AZ   | 1.8m/3.2m | 3.2m/4.2m             | 0.54m            | 0.16m <sup>3</sup>      | 8.7kg                  |
| 184923 | DP367AZ   | 2.1m/3.8m | 3.5m/4.8m             | 0.58m            | 0.20m <sup>3</sup>      | 10.4kg                 |

| DIMENTOIONO       |                     |                  |
|-------------------|---------------------|------------------|
| Stiles: 8 cm wide | Flange: 2.25cm wide | Treads: 8cm wide |

**150**ka LOAD RATING

## HEAVY INDUSTRIAL

## STYLE: Aluminium Dual Purpose 2 in 1 Ladder



#### Model DP406A7

• Versatile design - two ladders in one. Easily converts from a stepladder to a straight ladder.

#### **SPECIFICATIONS**

| M10SKU | Model No. | Size      | Max. Reach<br>Height* | Approx.<br>Width | Approx. Vol<br>per Unit | Approx<br>Shipping Wt. |
|--------|-----------|-----------|-----------------------|------------------|-------------------------|------------------------|
| 184927 | DP406AZ   | 1.8m/3.2m | 3.2m/4.2m             | 0.54m            | 0.16m <sup>3</sup>      | 9.5kg                  |
| 184928 | DP407AZ   | 2.1m/3.8m | 3.5m/4.8m             | 0.58m            | 0.20m <sup>3</sup>      | 11.4kg                 |
| 184929 | DP408AZ   | 2.4m/4.4m | 3.8m/5.4m             | 0.62m            | 0.25m <sup>3</sup>      | 13.4kg                 |

| BINIENCIONO       |                     |                  |
|-------------------|---------------------|------------------|
| Stiles: 8 cm wide | Flange: 2.25cm wide | Treads: 8cm wide |

#### STYLE: Aluminium Double-Sided Stepladder

Shoulder bolt and lock nut on top hinge; 4 solid aluminium rivets attach top to each stile Heavy gauge aluminium extruded top

Solid double-riveted construction

Heavy duty internal aluminium spreaders

Slip-resistant Traction-Tred® extra-deep treads

Thick side plates

Model T404A7

Full U-Channel bracing on bottom treads

Slip-resistant foot pad

for rigidity and ease of operation

SPECIFICATIONS

| SPECIFI | CATIONS   |      |               |                   |                         |                       |
|---------|-----------|------|---------------|-------------------|-------------------------|-----------------------|
| M10SKU  | Model No. | Size | Approx. Width | Approx.<br>Spread | Approx. Vol<br>per Unit | Approx<br>Shipping Wt |
| WITOSKO | WOUGH NO. | JIZC | Approx. width | Spicau            | per onit                | Shipping Wt           |
| 184924  | T403AZ    | 0.9m | 0.46m         | 0.73m             | 0.10m <sup>3</sup>      | 8.32kg                |
| 184925  | T404AZ    | 1.2m | 0.50m         | 0.92m             | 0.14m <sup>3</sup>      | 9.75kg                |

**DIMENSIONS** 

Top: 21cm x 36cm Stiles: 8cm wide Treads: 8cm wide Flange: 2.8cm wide

## PA208AZMODEL

330kg WORKING LOAD LIMIT (W.L.L.) - 1 person

#### STYLE: Aluminium Extension Plank

Locking mechanism sets the plank in 300mm increments

Moulded thermo-plastic spacer guides easy open/close action

Extruded cross member riveted with solid aluminium rivets

Made of 50mm deep box section extrusions

Heavy end flange/handles

· For use on telescoping multiladders and trestle ladders.

Note: When used on trestles, these planks must be used in conjunction with suitable guard rail protection in compliance with applicable governmental codes, ordinances, regulations and safe practice.

#### SPECIFICATIONS

|        |           |                 |               | Approx. | Approx.       | Approx.      |
|--------|-----------|-----------------|---------------|---------|---------------|--------------|
| M10SKU | Model No. | Closed Position | Open Position | Width   | Vol. Per Unit | Shipping Wt. |
| 213462 | PA208AZ   | 2.44m           | 3.96m         | 355mm   | $0.05 m^3$    | 18.5kg       |

#### DIMENSIONS

Inner Rails: 2.8m x 5cm Outer Flanged Rails: 4.8m x 5cm

#### STYLF: Aluminium Work Platform





#### Model AP-150TA7

- Extra-Wide Platform with Adjustable Legs
- Extendable length and adjustable height for greater versatility

#### **SPECIFICATIONS**

| M10SKU | Model No. | Length        | Width          | Platform<br>Height | Approx.<br>Volume<br>per Unit | Approx.<br>Shipping<br>Wt. |
|--------|-----------|---------------|----------------|--------------------|-------------------------------|----------------------------|
| 213478 | AP-150TAZ | 1.36m - 2.08m | 0.39m - 0.43mm | 0.55m-0.8m         | 0.07m <sup>3</sup>            | 11.0kg                     |

#### DIMENSIONS

Top: 0.93m x 0.27m - 1.5m x 0.28m

Highest Standing Level: 0.55m - 0.8m

## P-20AZMODFI

LOAD RATING

DOMESTIC

#### STYLE: Aluminium Work Platform



#### SPECIFICATIONS

| or Loil IoATIONS |           |        |       |                 |                    |              |  |  |  |  |
|------------------|-----------|--------|-------|-----------------|--------------------|--------------|--|--|--|--|
|                  |           |        |       |                 | Approx.            | Approx.      |  |  |  |  |
| M10SKU           | Model No. | Length | Width | Platform Height | Volume per Unit    | Shipping Wt. |  |  |  |  |
| 187520           | AP-20AZ   | 1.28m  | 0.4m  | 0.51m           | 0.06m <sup>3</sup> | 5.45kg       |  |  |  |  |

| Ton: 1m v ∩ 3m | Highest Standing Level: 0.51m |  |  |  |  |  |
|----------------|-------------------------------|--|--|--|--|--|

## STYLE: Aluminium Compact Extension Ladder





Heavy duty, self-aligning, free-swinging foot with slip-resistant



Adjustable lengths for easy access at multiple job heights



Easily transportable

**SPECIFICATIONS** 

| M10SKU | Model No. | Size       | Max. Reach Height* | Approx.<br>Vol per Unit | Approx.<br>Shipping Wt |
|--------|-----------|------------|--------------------|-------------------------|------------------------|
| 223797 | D1216-3AZ | 2.0m/4.15m | 5.3m               | 0.177m <sup>3</sup>     | 135kg                  |

|  | NS |  |
|--|----|--|
|  |    |  |
|  |    |  |

| Stiles: 7.6cm wide | Flange: 2.5cm wide | Rungs: 4.5cm wide | Base Width: 52.7cm outside feet |
|--------------------|--------------------|-------------------|---------------------------------|
|                    |                    |                   |                                 |

#### STYLE: Aluminium D-Rung Extension Ladder



Exclusive Alflo® rung joint means Twist-Proof performance

Non-marking end caps

Extra heavy duty I-beam stiles

Interlocking stiles

Slip-resistant Traction-Tred® D-rungs Heavy duty pulley with side rope

Rugged gravity clutch operates smoothly

Internal guides increase ease of operation

Heavy duty, self-aligning, free-swinging foot with slip-resistant tread and replaceable steel spur plate

Model D520-2AZ

#### SPECIFICATIONS

| M10SKU | Model No. | Size      | Max. Reach<br>Height* | Approx.<br>Vol per Unit | Approx.<br>Shipping Wt |
|--------|-----------|-----------|-----------------------|-------------------------|------------------------|
| 187518 | D520-2AZ  | 3.0m/5.2m | 6.2m                  | 0.27m <sup>3</sup>      | 16.3kg                 |
| 187519 | D524-2A7  | 3.6m/6.4m | 7.4m                  | 0.32m <sup>3</sup>      | 20.4kg                 |

**DIMENSIONS** 

Stiles: 8.25cm wide Flange: 3cm wide Rungs: 4.5cm wide Base Width: 48.5cm outside feet

## <u>AH2512AZ & AH22</u>10AZ MODEL

## STYLE: Aluminium Folding Attic Ladder



fitted feet for easy installation and correct fit

#### Model AH2510AZ

- · Provides easy access to attics, garages, and storage spaces
- · Lightweight easy to open, close and install
- Attractive will not splinter, decay or rust.
- Attic ladder Assist Pole included

Easy to install.

#### **SPECIFICATIONS**

|        |           |                |                  | Approx. | Approx.            | Approx.  |
|--------|-----------|----------------|------------------|---------|--------------------|----------|
| l      |           | Rough Opening  | Floor to Ceiling | Ladder  | Volume per         | Shipping |
| M10SKU | Model No. | Width x length | Height Range     | Width   | Unit               | Ŵt.      |
| 184938 | AH2210AZ  | 0.57 x 1.37m   | 2.34 to 3.12m    | 0.36m   | 0.19m <sup>3</sup> | 22.0kg   |

| DIMENSIONS         |                    |                  |  |  |  |  |  |  |
|--------------------|--------------------|------------------|--|--|--|--|--|--|
| Stiles: 7.3cm wide | Flange: 3.8cm wide | Treads: 8cm wide |  |  |  |  |  |  |

#### **SPECIFICATIONS**

|        |           |                |                  | Approx. | Approx.            | Approx.  |
|--------|-----------|----------------|------------------|---------|--------------------|----------|
|        |           | Rough Opening  | Floor to Ceiling | Ladder  | Volume             | Shipping |
| M10SKU | Model No. | Width x length | Height Range     | Width   | per Unit           | Wt.      |
| 218979 | AH2512AZ  | 0.63m x 1.37m  | 3.18m to 3.66m   | 0.36m   | 0.26m <sup>3</sup> | 26.5ka   |

#### MENCIONS

| DIMENSIONS         |                    |                  |  |  |  |  |  |
|--------------------|--------------------|------------------|--|--|--|--|--|
| Stiles: 7.3cm wide | Flange: 3.8cm wide | Treads: 8cm wide |  |  |  |  |  |

## STYLE: Aluminium Telescoping MultiLadder



#### Model MT-13AN

 Telescoping design for maximum versatility.

#### 4 Positions

Easily converts to:

- 1. Double-sided Stepladder
- 2. Stairway Stepladder
- 3. Telescoping Single Ladder
- 4. 2 Self-supporting Trestles (with Plank\*)

#### **SPECIFICATIONS**

| M10SKU | Model No. |    | Stepladder<br>Height | Single<br>Height | Stair<br>Height | Trestle<br>Height | Approx.<br>Width   | Approx.<br>Volume<br>per Unit | Approx<br>Shipping<br>Wt. |
|--------|-----------|----|----------------------|------------------|-----------------|-------------------|--------------------|-------------------------------|---------------------------|
| 243704 | MT13-AN   |    | 0.9 to               | 2.1 to           | 0.9 to          | 0.3 to            | 0.17m <sup>3</sup> | 0.17m <sup>3</sup>            | 14.3kg                    |
| 243705 | MT17-AN   | 20 | 1.5m<br>1.2 to       | 3.4m<br>2.7 to   | 1.5m<br>1.2 to  | 0.6m<br>0.3 to    | 0.20m <sup>3</sup> | 0.20m <sup>3</sup>            | 17.9kg                    |
|        |           |    | 2.1m                 | 4.6m             | 2.1m            | 0.9m              |                    |                               |                           |

| ИE |  |  |
|----|--|--|
|    |  |  |

| Stiles: 6.6cm wide | Flange: 2.5cm wide | Treads/Rungs: 2.5cm wide | Ladder Width: 40.6cm wide |
|--------------------|--------------------|--------------------------|---------------------------|
|                    |                    |                          |                           |

## SRST-72AZMODFI **450**kg WORKING LOAD LIMIT (W.L.L.)

### STYLE: Steel Rolling Scaffold

Can be used on industrial worksites



#### Model SRST-72A7

- · One-person assembly
- no tools required for quick setup and tear down.
- · Base pack:
  - 1.5m maximum deck height,
  - 3.5m maximum reach height\*.
- Tower
- Two base packs with guard rail and outriggers:
- 3.5m maximum deck height,
- 5.5m maximum reach height\*.
- \* Assumes a 1.7m person with a vertical 0.3m reach

#### DIMENSIONS

| 4 | DIMITIA | 310143    |               |                |                |                      |
|---|---------|-----------|---------------|----------------|----------------|----------------------|
| ı | M10SKU  | Model No. | Approx. Width | Approx. Length | Approx. Height | Approx. Shipping Wt. |
| ١ | 184937  | SRST-72AZ | 0.75m         | 1.87m          | 1.9m           | 65.09kg              |

## COMPONENT DIMENSIONS

| Component       | Quantity Included | Approx. Width | Approx. Length | Approx. Height |
|-----------------|-------------------|---------------|----------------|----------------|
| Frames          | 2                 | 0.74m         | 1.75m          | 3.8cm          |
| Arm Braces      | 2                 | 4.0cm         | 1.88m          | 45.4cm         |
| Plywood Deck    | 1                 | 0.72m         | 1.69m          | 3.8cm          |
| Locking Castors | 4                 | 12cm          | 25cm           |                |

ACCESSORIES (AVAILABLE SEPARATELY)

| M10SKU | Model No.  | Description                 | Approx.<br>Width | Approx.<br>Length | Approx.<br>Height | Approx.<br>Shipping Wt. |
|--------|------------|-----------------------------|------------------|-------------------|-------------------|-------------------------|
| 189917 | SRG-72AZ   | Guard Rail and Toeboard Kit | 0.73m            | 1.77m             | 1.07m             | 31.97kg                 |
| 189918 | SRO-72-4A7 | Outrigger Kit               | 457mm            | 527mm             | _                 | 17.01ka                 |

Note : Outriggers and Guard Rails are required when working height reaches 2m.

: Wheels for the outriggers come from second base pack.

## MWP-48AZMODEL 225kg WORKING LOAD LIMIT (W.L.L.)

## STYLE: Steel Mobile Adjustable Work Platform

Can be used on industrial worksites





#### Model MWP-48AZ

• Extra wide 25cm plank for secure standing and comfort



#### **SPECIFICATIONS**


|        |           |        |       |       | Approx.           | Approx.      |
|--------|-----------|--------|-------|-------|-------------------|--------------|
| M10SKU | Model No. | Height | Width | Depth | Volume Per Unit   | Shipping Wt. |
| 184936 | MWP-48AZ  | 1.27m  | 1.17m | 0.65m | 0.9m <sup>3</sup> | 27.22kg      |

#### PLANK DIMENSIONS

| Narrow Plank: Length 1.09m, Width 15cm | Wide Plank: Length 1.09m, Width 25.4cm |
|--|--|
|  |  |

## CARS-60AZMODEL 225ka WORKING LOAD LIMIT (W.L.L.)

## STYLE: Aluminium Compact Scaffold Can be used on industrial worksites



Model CARS-60A7

- Strong, lightweight aluminium scaffold.
- · Maximum platform height: 1.5m
- Maximum reach height\*: 3.5m
- Install guard rail (CARG-60AZ) for extra safety whilst working at 1.5 metres.

<sup>\*</sup>Assumes a 1.7m person with a vertical 0.3m reach



Compact design for easy mobility and storage



Guardrail, available separately, provides extra safety erected - Model CARG-60AZ

#### **SPECIFICATIONS**

| M10SKU | Model No. | Approx. Width | Approx. Length | Approx. Height | Approx.<br>Shipping Wt. |
|--------|-----------|---------------|----------------|----------------|-------------------------|
| 213463 | CARS-60AZ | 0.76m         | 1.63m          | 1.53m          | 33.1kg                  |

#### ACCESSORIES (AVAILABLE SEPARATELY)

| M10SKU  | Model No.   | Description     | Approx.<br>Width | Approx.<br>Length | Approx.<br>Height | Approx.<br>Shipping Wt. |
|---------|-------------|-----------------|------------------|-------------------|-------------------|-------------------------|
| WITOSKO | WIOUCI IVO. | Description     | vviutii          | Longin            | Height            | Jilipping Wt.           |
| 213464  | CARG-60A7   | Guard Rail Pack | 0.76m            | 1.63m             | 1.00m             | 14 5kn                  |

## AC18MTAZ

#### Platform



Slip-resistant surface. Aluminium construction. Kicks out of way for easy climbing. 150kg load capacity.

## **User Installed Only**

| M10SKU              | Kit No   | Approx.<br>Shipping Wt. |  |  |  |
|---------------------|----------|-------------------------|--|--|--|
| 184940              | AC18MTAZ | 2.04kg                  |  |  |  |
| Fits on             |          |                         |  |  |  |
| All MT OOA 7 Sorios |          |                         |  |  |  |

## AC24AZ

#### Multipurpose Project Tray



Project tray conveniently holds tools, paints and supplies. Made for Werner multiladders and stepladders. Attaches easily; works at multiple heights.

#### User Installed Only

|                           |                  | •                |  |  |  |
|---------------------------|------------------|------------------|--|--|--|
|                           |                  | Approx. Shipping |  |  |  |
| M10SKU                    | Kit No           | Wt.              |  |  |  |
| 184942                    | AC24AZ           | 1.27kg           |  |  |  |
| Fits on                   |                  |                  |  |  |  |
| MT-00AZ Series Industrial |                  |                  |  |  |  |
| & He                      | avy Industrial 9 | Stenladders      |  |  |  |

## AC19-2AZ

#### Extension Ladder Covers



Helps prevent damage to support surfaces. Designed to 'snap' over extension ladder stile end caps. Resists paints, stains, thinners and solvents.

#### User Installed Only

| M10SKU   | Kit No   | Approx. Shipping Wt. |  |  |  |
|--|----------|----------------------|--|--|--|
| 184939   | AC19-2AZ | 0.54kg               |  |  |  |
| Fits on  |          |                      |  |  |  |
| All Fibreglass and Aluminium Extension ladders |          |                      |  |  |  |
| (except D500A7)                                |          |                      |  |  |  |

Shipping quantity 1 pair per unit; (6) units per carton.

## AC78AZ

#### Ouickclick™ Stabiliser



Span: 1.1m. Standoff: 25cm Requires no tools. Spring-loaded locking latch makes it easier and quicker to install/remove than any other stabiliser on the market. Scuff resistant rubber end caps protect work surface. Stabiliser comes with instructions. Paint can hook included.

#### User Installed Only

| M10SKU           | Kit No                                 | Approx. Shipping Wt. |  |  |  |
|------------------|--|----------------------|--|--|--|
| 184941           | AC78AZ                                 | 2.90kg               |  |  |  |
|                  | Fits on                                |                      |  |  |  |
| For use          | For use on Singles and Extensions with |                      |  |  |  |
|                  | 3.2cm round rungs                      |                      |  |  |  |
| 3.8cm flat rungs |  |                      |  |  |  |
| 4.4cm flat rungs |  |                      |  |  |  |
| 4.1cm flat rungs |  |                      |  |  |  |

#### Not for use on MT-00AZ Series

Shipping quantity (1) unit per carton.

#### DIITY & LOAD RATINGS

Ladders manufactured to Australian and New Zealand Standards AS/NZS 1892 must clearly display a Duty Rating and a Load Rating.

These are clearly defined in AS/N7S 1892.1

- Portable Ladders, Metal.
- · Section 1.6 Definitions
- · Section 2.2 Ratings

#### I OAD RATING:

Load Rating is the maximum load including the weight of the user, materials and tools.

Domestic ladders shall have a Load Rate not less than 100kg. Industrial ladders shall have a Load Rate not less than 120kg.

#### DIITY RATING:

The Duty Rating is assigned by the manufacturer based on the design capabilities of the ladder. There are 2 Duty Ratings - Domestic and Industrial

#### **DOMESTIC** DUTY RATING

A ladder designed to be used by a householder for construction, maintenance and repairs carried out at a private dwelling for non-commercial purposes.

Domestic Duty Rated ladders must not be used on commercial or industrial sites.

#### INDUSTRIAL DUTY RATING

Any ladder other than a Domestic ladder

Industrial Duty Rated ladders are suitable for use on industrial and commercial work sites.

Industrial Duty Rated ladders can be used in domestic and industrial settings.

| DUTY RATING | LOAD RATINGS              |       |                               |
|-------------|---------------------------|-------|-------------------------------|
| DOMESTIC    | 100kg (min), 120kg, 170kg |       |                               |
| INDUSTRIAL  | 120kg (min)               | 135kg | 150kg, 170kg,<br>200kg, 225kg |



Werner Co. Australia 70 Fulcrum Street Richlands QLD 4077 Australia Ph: 0800 529 6709 Email: salesnz@wernerco.nz www.wernerladder.co.nz

POP88 52 ©2014 Werner Co. Rev A 9/14