

Eaton DSD925 SA S635

Catalog Number: DSD925 SA S635

Eaton Crouse-Hinds series DSD selector switch cover and device sub-assembly, 10A, Copper-free alum, 3 pos, 2 circuit, Momentary contact counterclockwise oper, spring return to center, maintained contact, clockwise oper, fact seal, 600 Vac

General specifications

Product Name	Catalog Number
Eaton Crouse-Hinds series DSD selector switch cover and device sub-assembly	DSD925 SA S635
	UPC
	782274959184
Product Length/Depth	Product Height
0.001 in	0.001 in
Product Width	Product Weight
0.001 in	1.76 lb

Certifications and compliances

Area classification

Hazardous/Classified Locations

Standards type

NEC/CEC

NEC hazardous rating

Class I, Division 1

Class I, Division 2

Class II, Division 1

Class II, Division 2

Class III

NEMA Rating

3

7

9

Product specifications

Voltage rating

600 Vac

Normal position

3 position, 2 circuit

Amperage Rating

10A

Material

Copper-free aluminum

Special features

Momentary contact counterclockwise operation, spring return to center, maintained contact clockwise operation, factory sealed

Type

Maintained contact

Resources

Catalogs

[DSD and DSDX Cover and Device Sub-assemblies catalog page](#)

Certification reports

[DSD Explosionproof Cover and Device Sub-assemblies UL certification](#)

[DSD Explosionproof Cover and Device Sub-assemblies Canadian certification](#)

Installation instructions

[IF 1424 - DSD, GFS, CPS and ENR Series Replacement Covers](#)

[IF 1929 - Toggle Operator for EDS, EDSX, EFD, DSD and DSDX Series](#)

[IF 899 - EDSX, EDS, EFS, DSDX and DSD Control Stations](#)

Specifications and datasheets

[Eaton Specification Sheet - DSD925 SA S635](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)