

## FEATURES

- Wide measuring range (Brix 0 ~ 53%)
- Refractive index measurement (RI)
- Temperature measurement (°C/°F)
- Ambient temperature compensation (ATC)
- Brix or RI high/low limit value alarm function
- Zero calibration with distilled or deionized water
- Friendly operation and easy to use
- Wide and dual display LCD and backlight function
- Reliable water resistant (IP65)
- Auto power off function
- Data memory and read function

## RS PRO Brix Meter

RS Stock No.: 2107487, 2107617



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## APPLICATIONS

- Food industry: Beverages, fruits and sweets
- Industry: Monitoring of lubricants in machines and quality control
- Agriculture: Determination of the degree of ripeness of fruit for quality control in harvesting

## General Specifications

<b>Sensor</b>	Photodiode arrays
<b>Measuring Function</b>	Brix (%) Temperature (°C/°F) Refractive index (RI)
<b>Brix Range</b>	0.0 ~ 53.0% (10 ~ 40°C/50 ~ 104°F Automatic temperature compensation)
<b>RI Range</b>	1.3329 ~ 1.4265
<b>Temperature Range</b>	4 ~ 60°C (39.2~140°F)
<b>Accuracy (Water at 23°C /73.4°F)</b>	Brix: ±0.2%, Temperature: ±1°C/°F RI: ±0.0003
<b>Resolution</b>	Brix: 0.1%, Temperature: 0.1°C/°F, RI: 0.0001
<b>Data memory Capacity</b>	99 sets. (Direct reading from LCD display)
<b>Operation Temperature Range</b>	10~40°C (50 ~ 104°F), Less than 85%RH
<b>Store Temperature Range</b>	0~50°C (32 ~ 122°F), Less than 85%RH
<b>Response Time</b>	3 seconds
<b>Accessories</b>	Instruction manual, Battery, One sample vial, Two transfer plastic pipettes, Carrying case

## Mechanical Specifications

<b>Dimensions</b>	148mm x 78mm x 50mm
<b>Width</b>	78mm
<b>Length</b>	148mm
<b>Height</b>	50mm
<b>Weight</b>	Approx. 250g

## Electrical Specifications

<b>Battery</b>	AAA batteries x 4
----------------	-------------------

## Protection Category

<b>International Protection Class</b>	IP65 water resistant
---------------------------------------	----------------------

## Additional Information

<b>EAN</b>	8000126233360
<b>Custom Tariff Number</b>	85371098

## Classification

<b>eCl@ss</b> (Version)	
<b>UNSPSC</b> (Version)	

## Approvals

<b>Compliance/Certifications</b>	CE

## Similar Products

Stock No.	Brand	Product Name	Attribute 1	Attribute 2	Attribute 3
XXX-XXXX	RS PRO				

Connection Diagrams / Assembly Diagrams / Illustrations / Accessories