


ABS

10KG · 20KG · 30KG · 50KG Carbon Dioxide Trolley



MODEL	14311	14321_6	14322	14352
Capacity	10KG	20KG	30KG	50KG
Extinguishing Agent	Carbon Dioxide			
Test Standard	EN1866			
Operation Method	Stored Pressure			
Propellant	CO2	CO2	CO2	CO2
Discharge Distance	4M	4M	4M	4M
Discharge Time	17SEC	32SEC	35SEC	52SEC
Height	980MM	970MM	1140MM	1435MM
Width	370MM	400MM	520MM	650MM
Depth	1060MM	600MM	1150MM	1400MM
Total Weight	38KG	70KG	85KG	156KG
Operating Temperature	-30°C to 60°C			
Working Pressure	60 BAR			
Test Pressure	250 BAR			
Fire Rating	144 IV B	233 IV B	233 IV B	233 IV B
Part No.	FEM-AB-C10	FEM-AB-C20	FEM-AB-C30	FEM-AB-C50



Wheelmark

Information

Effective against **class B fires** involving flammable liquids, solvents, oils, paints, thinner and liquifieable solids.

Instructions for use

1. Read instructions before using to ensure that you have selected the correct fire extinguisher for the fire you intend to fight.
2. Unroll hose.
3. Pull safety pin and turn on valve.
4. Aim at fire and squeeze handle

Ensure that extinguisher is located close to the work area and operators are trained in the use of extinguishers.