



Main

| | |
|---------------------------|-------------------------------------|
| Range of product | AvatarOn C |
| Product or component type | Switched socket |
| Device application | Power supply |
| Device presentation | Basic element with complete housing |
| Colour tint | White |
| Main colour tint | White |

Complementary

| | |
|--------------------------------|--------------------|
| Rated current | 13 A socket-outlet |
| [Ue] rated operational voltage | 250 V AC 50/60 Hz |
| Socket number | 1 |
| Outlet standard | British |
| Number of gangs | 1 gang |
| Material | PC (polycarbonate) |
| Device mounting | Surface |
| Fixing mode | By screws |
| Height | 86 mm |
| Width | 86 mm |
| Depth | 30 mm |

Environment

| | |
|-------------------------|------|
| IP degree of protection | IP20 |
|-------------------------|------|

Packing Units

| | |
|------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.0 cm |
| Package 1 Width | 8.6 cm |
| Package 1 Length | 8.6 cm |
| Package 1 Weight | 76.0 g |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant with Exemptions |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

| | |
|-----------------------------|--|
| Circularity Profile | No need of specific recycling operations |
| Halogen content performance | Halogen free plastic parts product |
