

FEATURES

- Portable isolation transformer
- 5-minute short time
- Primary voltage rating of 230 V
- Secondary voltage rating of 230 V
- Power rating of 1.5 kVA
- 2 x 16 A output current
- Schuko plug and socket type
- Weight of 18 kg
- Dimensions of 350 mm x 242 mm x 353 mm
- Operating frequency range of 50 - 60 Hz
- Stand-alone mounting

RS PRO, 1.5kVA Portable Isolation Transformer, 230V ac, 2 x 16A

RS Stock No.: 122-6721



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

This standalone RS PRO portable isolation transformer can be used to isolate a standard European 230 V mains voltage supply. It has a high-quality design that's light, robust and is made with your safety in mind.

General Specifications

Type	Portable transformer
Enclosure	GRP- colour yellow
Applications	Transmission, distribution and utilization of alternating current electric power

Electrical Specifications

Power Rating	3.0KVA
Continuous Rating	1.5KVA
Primary Voltage Rating	230V ac
Secondary Voltage Rating	230V
Output Current	2 x 16A
Minimum Operating Frequency	50Hz
Maximum Operating Frequency	60Hz
Socket Type	Schuko
Plug Type	Schuko
Thermal Cut-out	10A

Mechanical Specifications

Mounting Type	Stand Alone
Dimensions	350mm x 242mm x 353mm
Length	350mm
Width	242mm
Depth	353mm
Weight	18kg

Protection Category

IP Rating	IP44
------------------	------

Approvals

Compliance/Certifications	EN61340
Standards Met	BS EN 61558, BS EN 61558-20-23



