



Datasheet

RS PRO UNCOATED ZigZag STAINLESS STEEL CABLE TIES

EN



Technical Information:

Material: Stainless Steel Grade 316

316 grade stainless steel, for extra corrosive environments

Working Temp.: -80°C to +500°C

Description: Entirely Metallic

Flammability: Fireproof

Other Properties: UV-resistant

Product Feature: The cable ties are self locking with a roller ball head, making them fast and easy to secure. The zig zag design maintains installed tension on surfaces, helping to reduce movement and slips. Uncoated version for high temperature applications.

Applications: Ideal for petrochemical, industries, power stations, mining, ship-building, offshore, and other aggressive environments.

Specification

RS CODE	EASE CODE	LENGTH		WIDTH		TICKNESS		MAX. BUNDLE DIAMETER	
		mm	inch	mm	inch	mm	inch	mm	inch
	CT-SS-ZZ-100/4.6UC	100	3.9	4.6	0.18	0.26	0.010	25	0.99
	CT-SS-ZZ-125/4.6UC	125	4.9					31	1.23
	CT-SS-ZZ-150/4.6UC	150	5.9					38	1.48
	CT-SS-ZZ-200/4.6UC	200	7.9					50	1.97
	CT-SS-ZZ-360/4.6UC	360	14.2					90	3.55
	CT-SS-ZZ-520/4.6UC	520	20.5					130	5.13
	CT-SS-ZZ-200/7.9UC	200	7.9	7.9	0.31	0.26	0.010	50	1.97
	CT-SS-ZZ-360/7.9UC	360	14.2					90	3.55
	CT-SS-ZZ-520/7.9UC	520	20.5					130	5.13